

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 34 & 35 T25½S R3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9748)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 2, 3, 34, & 35, with brass cap mkd:

T25½S R3E  
S34 | S35  
S3 | S2  
T26S  
1931

from which

- A fir, 32" dia., bears N.59°E., 68 lks., mkd: T25½S R3E S35 BT.
- A fir, 56" dia., bears S.51°E., 115 lks., mkd: T26S R3E S2 BT.
- A fir, 38" dia., bears S.30°W., 113 lks., mkd: T26S R3E S3 BT.
- A fir, 38" dia., bears N.80°W., 87 lks., mkd: T25½S R3E S34 BT.