

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION WC 1/4 Cor. Secs. 2; & 35 T25 1/2 S R3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9748-9)

A fir, 35" dia., for 1/4 sec. cor. mkd.

1/4 S 35 on N and

S 2 on S side

from which

A fir, 24" dia., bears N.8°E., 81 lks., mkd: 1/4 S35 BT.

A fir, 32" dia., bears S.21°E., 52 lks., mkd: 1/4 S2 BT.

Kristian DeGroot, PLS 1941 - For: USFS - Crew Les Fanning, Matt Dixon, & Aaron Fanning - March 1998 - C.S. File 65/20-8

Found - Original corner tree, a 35" Fir snag, ± 22 ft. tall with healed faces on the North and South sides.
27" Fir bears N.8°E., 53.5 ft. with a healed blaze.
1931

34" Fir snag ± 20 ft. tall bears S.15°E., 34.0 ft. with a healed blaze (Rec. S.21°E.) 1931

Set - 2 1/2"x30" alum. pipe, 24" in the ground in a 48" dia. mound of stone, base to top with a 3 1/4" alum. cap stamped:

U.S. DEPT. OF AGRICULTURE FOREST SERVICE

T26S R3E

1/4 S2 RM

← N.86°22'W

15.00 FT.

bears S.86°22'E., 15.00 ft.

10" Fir bears S.10°W., 18.0 ft. scribed "1/4 S2 BT" with a brass washer stamped "PLS 1941" nailed into the lower blaze

Paint a 6" red band and BT face red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BTs.