

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9751-2)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 25, 26, 35, & 36, with brass cap mkd:

T26S|R3E  
S26|S25  
S35|S36  
1930

from which

- A pine, 12" dia., bears N.57°E., 17 lks., mkd: T26S R3E S25 BT.
- A fir, 20" dia., bears S.59°E., 57 lks., mkd: T26S R3E S36 BT.
- A pine, 32" dia., bears S.79°W., 42 lks., mkd: T26S R3E S35 BT.
- A fir, 32" dia., bears N.15°W., 32 lks., mkd: T26S R3E S26 BT.