

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9760-1)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 1, 2, 11, & 12, with brass cap mkd:

T26S	R3E
S2	S1
S11	S12
1930	

from which

- A fir, 17" dia., bears N.24°E., 70 lks., mkd: T26S R3E S1  
BT.
- A fir, 48" dia., bears S.38°E., 85 lks., mkd: T26S R3E S12  
BT.
- A fir, 40" dia., bears S.28°W., 68 lks., mkd: T26S R3E S11  
BT.
- A fir, 50" dia., bears N.25°W., 92 lks., mkd: T26S R3E S2  
BT.