

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 36; 30 & 31 T26-4E

Alias _____ Description (Sec 30 T26-4E = PB 41)
Alias _____ Description (Sec 31 T26-4E = PB 42)
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9735-6)

Set an iron post, 3 ft. long, 2" dia., 18" in the ground, to bedrock, for cor. of secs. 25, 30, 31, & 36, with brass cap mkd

T26S
R3E|R4E
S25|S30
S36|S31
1930

from which

- A cedar, 15" dia., bears N.84°E., 27 lks., mkd: T26S R4E S30 BT.
- A fir, 20" dia., bears S.37°E., 33 lks., mkd: T26S R4E S31 BT.
- A fir, 12" dia., bears S.49°W., 66 lks., mkd: T26S R3E S36 BT.
- A cedar, 16" dia., bears N.28°W., 48 lks., mkd: T26S R3E S25 BT.