

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 12; 6 & 7 T26-4E

Alias _____ Description (Sec 6 T26-4E = PB 37)
Alias _____ Description (Sec 7 T26-4E = PB 38)
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9740-1)

Set an iron post, 3 ft. long, 2" dia., 25" in the ground, for cor. of secs. 1, 6, 7, & 12, with brass cap mkd:

T26S
R3E|R4E
S 1|S 6
S12|S 7
1930

from which

- A fir, 38" dia., bears N.10°E., 21 lks., mkd: T26S R4E S6 BT.
- A fir, 30" dia., bears S.40°E., 42 lks., mkd: T26S R4E S7 BT.
- A fir, 36" dia., bears S.54°W., 194 lks., mkd: T26S R3E S12 BT.
- A fir, 28" dia., bears N.49°W., 111 lks., mkd: T26S R3E S1 BT.