TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 042020

PRIMARY CORNER DESCRIPTION NW Cor. Shrum DLC #42

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Surveyed by Aaron Bowser, Contract #68 dated April 1856

Set post, from which
A W.Oak 12" dia., bears N.80°W., 112 lks. dist.
Raised mound with trench as per instructions.

C.E. Roberts - July 13, 1911 - Field Book 57 Page 55

Set at stump of witness tree to Cl. 42 measured S.80°E., 112 lks and set iron bar 1¼ x 18".

Doug. County Surveyors Office - Vernon Tracy - Mike Stone; Jack Heritage - Feb/March 1966 - C.S. File 54/7-54

Found - 1¼" Steel shaft by Roberts in 1911.
No trace of original BT.
Measure from the ¼ cor. of secs. 18 & 19, 443.5 ft. as recorded in orig. DLC field notes and find that it checks within less than a foot.
Set Brass cap flush with ground & mkd: County Surveyor Office
1966 _____
N.W. Corner DLC /42 T26SR3W
Brass cap lies on N. edge of asphalt street, course E & W.
No BTs available, we use the following bearing objects:
Power Ple bears S.14°W., 38.8 ft. Pole #Copco B9673.
SW Corner of imitation brick house bears N.10°W., 8.1 ft.
NW Corner of concrete sidewalk 4.0 ft. wide bears S.47°E., 72.5 ft.

Found OK, August 1992 - Bruce Shaner Partition Plat 1992-0067 FD. Ok by K. DeGroot, Feb. 2006 - M149-48

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 10/25/2007 - C.S. File 67/24-39

NW cor. DLC 42 found ok, imitation brick house now sided with T-111 plywood.