

PRIMARY CORNER DESCRIPTION SW Cor. Shrum DLC #45

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Aaron Bowser, Contract #68 dated April, 1856 - (DCSO DLC Records Pg. 272)

Set post, from which
 A B.Oak 12" dia., bears N.85°E., 19 lks.
 Deposited stone 8x11.
 Raised mound with trench as per instructions.

Douglas Co. Surveyors Office - Randall Smith, Deputy - Stephen Flause - 12/12/2002 & 1/9/2003 - C.S. 66/48-24A&B

Found - 12" now 36" dia., 3 ft. high hollowed out B.Oak stump old blaze with axe & circular scribe marks visible.

Set - 2½" dia., by 32" long iron pipe is set from blaze S.85°W., 12.5 ft. DOUGLAS CO. SURVEYORS OFFICE

R	DLC
3	45
W	
2002	

New - 8" dia., I.Cedar double blazed & scribed "SW DLC 45 CS BT" bears S.86½°W., 43.7 ft.
 14" dia., W.Oak double blazed & scribed "SW DLC 45 CS BT" bears S.26°E., 69.9 ft.
 27" dia., W.Oak double blazed & scribed "SW DLC 45 CS BT" bears N.67°E., 87.5 ft.
 5/8" iron rod bears N.8¼°E., 112.1 ft.
 South gate post bears N.80°E., 15 ft.
 Compass decl. 17½°E.

Note, this is a rewritten renewal corner renewed 12/12/2002 Following positions are for location purposes only

NOT SURVEY GRADE

Equipment: Trimble GEOEXPLORER 3 System
 File: R121620A
 Point Name: T26SR3W SW45

	<u>1927</u>		<u>1983</u>
OCS	N 593772	E 1307973	N E
Latitude:	43°15'59.3"		Latitude: °' "
Longitude:	123°05'55.2"		Longitude: °' "
Offset to corner?	no		

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 2/6/2008 - C.S. File 67/25-11

Fd. Ok, as per 2002 DCSO rec.