TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 045060

PRIMARY CORNER DESCRIPTION East SE Cor. Shrum DLC #45

Alias_____ Description_____
Alias_____ Description_____
Alias_____ Description_____
Alias_____ Description_____

Original - Aaron Bowser, Contract #68 dated April, 1856

Set post, from which
A W.Oak 6" dia. bears N.40°W., 23 lks.
A B.Oak 8" dia., bears S.80°W., 20 lks.

Doug. County Surveyors Office - Vernon Tracy - Mike Stone; J. Layne; Jack Heritage - Feb. 1966 - C.S. File 54/7-25

Found - Orig. 6" now 11" W.Oak N.40°W., 15.2 ft., Open & find "5 BT", scribe reversed.
Orig. 8" now 8" B.Oak S.80°W., 13.2 ft., down, dead and rotten. No scribe found.
Set brass cap at cor. mkd: County Surveyors Office, 1966
T26S R3W E.SE. Cor. DLC 45_____/
New BTs - 12 W.Oak S.8°W., 5.9 ft. mkd.: E.SE. DLC 45 CS BT.
12" D.Fir S.67°E., 23.1 ft. mkd: E.SE. DLC 45 CS BT.
This corner lies approx. 250 ft. East of Int. "L" Corner.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 12/18/2002 - C.S. File 66/48-21

Found - 1966 DCSO brass cap/iron pipe protrudes 7" out of ground.
6" now 10" dia., down & rotting W.Oak with a previously opened unhealed blaze no mark found bears N.40°W., 15.2 ft. to root hole (OBT)
Orig. SW BT now gone.
12" now 13" dia., W.Oak with a fully healed blaze, bears S.8°W., 5.9 ft. (1966)
12" now 20" dia., 2 ft. high D.Fir stump with fully healed blaze bears S.67°E., 23.1 ft. (1966)
New - 13" dia., D.Fir double blazed & scribed "ESE DLC 45 CS BT" bears S.26½°E., 22.0 ft.
7" dia., W.Oak double blazed & scribed "ESE DLC 45 CS BT" bears N.26°W., 1.0 ft.
10" dia., W.Oak double blazed & scribed "ESE DLC 45 CS BT" bears N.55½°E., 13.2 ft.
Compass decl. 17½°E.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 1/9/2008 - C.S. File 67/25-6

FD. Ok, 3 live BTs, 7" W.Oak (N.26°W., 1.0 ft.) now down.