

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 046010

PRIMARY CORNER DESCRIPTION NE Cor. Wimberly DLC #46

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Aaron Bowser, Contract #68 dated April, 1856  
-----  
Set post in prairie, deposited stone 12x15.  
Raised mound with trench as per instructions.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack Heritage - Feb./Mar. 1966 - C.S. File 54/7-51  
-----  
From the ¼ cor. of secs. 19 and 20, we measure South 4.86 chains, 320.8 ft., which is the record bearing and distance in orig. DLC notes for the beginning corner of DLC #46.  
Found - 14" x 10" stone and faint "4" mkd. on top. Orig. notes call for stone to be 12 x 15. Corner falls at fence corner, fences N-S-W.  
Set brass cap at cor. mkd: County Surveyors Office 1966  
T26S R3W N.E. Cor. DLC 47 |  
New BTs - 10" W.Oak S.89°W., 92.2 ft. mkd. N.E. DLC 46 CS BT.  
11 W.Oak N.34°W., 109.6 ft. mkd. N.E. DLC 46 CS BT.

Found OK, Sept. 1996 by K. DeGroot - Vol. 19, Pg. 12 A & B,  
Buck Rock Subdivision  
Fd. Ok by K.DeGroot, July 1997 - 1997-0126

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause -  
2/5/2008 - C.S. File 67/25-11  
-----  
Fd. Ok with these exceptions:  
10" now 14" W.Oak, fully healed double blaze, bears S.89°W., 92.2 ft. (agrees w/rec)  
11" now triple trunk W.Oak most southerly trunk is 17" dia., & shows fully healed double blaze, center of root crown bears N.41¼°W., 110.8 ft. (Rec. N.34°W., 109.6 ft.)