

PRIMARY CORNER DESCRIPTION SW Cor. Wimberly DLC #46

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Surveyed by Aaron Bowser, Contract #38 dated April, 1856  
-----

Set post, from which

A W.Oak 12" dia., bears N.50°E., 40 lks.

Raised mound with trench as per instructions.

Doug. County Surveyors Office - Vernon Tracy, Mike Stone;  
Jack Heritage - Feb/March 1966 - C.S. File 54/7-52  
-----

After diligent search, we fail to find any trace of original SW corner DLC #46. The actual corner would fall in cemetery. From the tie to NW corner DLC 43 in the original field notes, being 3½ chs. or 231.0 ft. west of the NW corner DLC 43, we measure 185 ft. and:

Set WITNESS CORNER in the East fence of the cemetery, 46.0 ft. East of actual corner which falls 46.0 ft. inside cemetery for Wit. Cor. Set Brass cap at cor. mkd:

County Surveyor's Office, 1966

T26S R3W Wit. Cor. SW DLC 46/ 46 ft. to Cor.

New BTs - 19" D.Fir S.10½°E., 81.5 ft. mkd: W.C. SW DLC 46  
CS BT.

26" D.Fir N.17°E., 18.0 ft. mkd. W.C. DLC 46 CS BT.

Doug. County Surveyors Office - Gregory Quibell, Deputy -  
Randy Smith - March 30, 1982 - C.S. 61/30-20  
-----

Found - 1½" I.P. with 1966 DCSO brass cap. Cap protrudes approx. 9" above ground & is in the east fence of "Wimberly Family Cemetery".

26" now 31" Fir with well healed blaze bears N.1°W., 18.0 ft. (Rec. N.17°E., was apparently taken with compass near the fence. By doing the same, I agree with rec. bearing. My bearing (N.1°W) was taken by offsetting 10.0 ft. east from the brass cap & the center of the 31" Fir.

Approx. 20" rotted Fir stump which is possibly the 19" D.Fir per 1966 renewal, bears S.10°E., 81.5 ft. which again matches record with my compass near fence. No scribing or face visible.

No original evidence found.

New Accessories:

9" Fir scribed "X CS BT" in double blaze bears N.29°W.,  
66.3 ft.

(Cont. Next Page)

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 046030

PRIMARY CORNER DESCRIPTION SW Corner DLC #46

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

10" Fir scribed "X CS BT" in double blaze bears  
N.10°E., 74.9 ft.  
12" Fir scribed "X CS BT" in double blaze bears N.54°E.,  
84.8 ft.  
4½" round knob on top of tombstone marked "Mrs. A.J.  
Greenman died May 9, 1907" bears S.52°W., 36.9 ft.  
Bearings shown for new bearing objects were taken at the  
object end rather than near the fence at the brass cap end of  
their respective lines. (Sketch in the C.S. file)

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause -  
1/8/2008 - C.S. File 67/25-5  
-----  
Fd. OK, 3 live BTs from 1982 DCSO renewal.

FD BC K. DeGroot, 7/2011 - M162-50