

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12 of T26-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 10 Page 4345)

Set post, cor. to secs. 1, 12, 6 and 7, from which
A R. Fir 15" dia. bears N.10°W., 83 lks. dist.
A R. Fir 23" dia. bears N.37°E., 100 lks. dist.
A Laurel 7" dia. bears S.51°E., 145 lks. dist.
A Laurel 5" dia. bears S.43°W., 187 lks. dist.

H.L. Eppstein, Doug. Co. Surveyor - Bert Lane; N.E. Richardson
April 12, 1921 - Field Book 54 Pages 64-66

Reestablished corner from 2 old BTs.
Set 4 x 4 x 40" Cedar Stake.
Marked 2 new BTs:
15" R. Fir bears S.80°E., 60 lks.
12" Cedar bears S.4°W., 15 lks.
Two old BTs:
30" R. Fir bears N.10°W., 83 lks. dist.
36" R. Fir bears N.26°E., 83 lks. dist.

Douglas Co. Surveyors Office - Ray Tracy; Mike Stone; J. Layne
February 1, 1966 - C.S. File 54/7-14

Found - Burned Cedar stump only remaining evidence of cor.
12" now 16" Cedar S.4°W., 9.9 ft., open & find
"26BT" scribe and reverse.
All other BTs gone.
Set brass cap at cor. mkd: County Surveyors Office 1966
T 26 S S 1 | S 6
R4W S 12 | S 7 R3W
(12" in ground and build mound of stone.)
New BT - 14" D. Fir S.88°W., 102.8 ft. mkd: T26S R4W S12 CS BT
No other trees available.
Corner lies in N-S fence approx. 180 ft. South of
Creek, course SE, curving to East. A 1¾" Axle
shaft bears N.85°W., 1.8 ft.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause -
2/20/2008 - C.S. File 67/25-15

Found - 2½" dia., brass cap properly marked on 1¼" O.D. iron
pipe, loosely set in scattered pile of stone.
BC/IP projects 18" above ground.
A 1¾" dia., x 33" long splined axle is fd loose on
top of ground on West side of BC/IP.
continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12 of T26-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Burnt cedar stump, approx. 2 ft. tall, indeterminate dia., show old axe marks on north side, bears S.4°W., 9.9 ft. (agrees w/rec) 1921 BT
14" now 30" dia., x 2 ft. tall D.Fir stump, chopped into top and fd partial scribing on old face, bears S.88¾°W., 100.4 ft. (Rec. S.88°W., 102.8 ft.) 1966 BT
New - 23" dia., D.Fir double blazed & scribed "T26S R4W S12 CS BT" bears S.89½°W., 102.5 ft.
14" dia., madrone - pistol butt - double blazed & scribed "T26S R4W S1 CS BT" center of root crown bears N.34½°W., 97.7 ft.
Note - Corner lies on steep north facing slope in N-S fence line. Mountain-side pasture in all quadrants. Splined axle is left on top of ground on West side BC/IP.
Compass decl. 16¼°E.