

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31; & S. 6 of T27-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 10 Page 4350)

Set ¼ sec. post, from which
 A W.Oak 8" dia., bears N.5°W., 350 lks. dist.
 An Ash 8" dia., bears S.38°E., 164 lks. dist.

Ben B. Irving - Ed Russell; W.E. Chapman - Dec. 26, 1922
C.S. File 4/29; Vol. 3 Page 139A

Identified location from original BTs. Drove 1¼" iron pipe
for corner from which
 Fir 16" dia., bears S.5°54'E., 144 ft.
 Fir 18" dia., bears N.31°33'E., 66 ft.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone;
Jack Heritage - Feb. 1966 - C.S. File 54/7-59

Found - 1¼" O.D. Iron pipe at fence corner.
 18" now 26" D.Fir N.31½°E., 66.0 ft. (face) shows
 very good, upper & lower scars. Do not open.
 Stump hole to SE, probably other BT.
New BT - 6" D.Fir S.58°W., 16.5 ft. mkd. ¼ S6 CS BT.
This corner lies at fence corner with fences S-E and W. and
40 ft. west of creek, course N.

Mark Smalley - For: Roseburg Resources - 7/2001 - M 138-49

Found - 1½" iron pipe.
 38" (26") Fir N.31½°E., 66.0' healed.
 18" (6") Fir S.58°W., 16.5' healed
Scribed - 5" Fir S.20°E., 21.3' "¼ S BT"
 12" Fir S.25°W., 26.4' "¼ S BT"

Found OK by K. DeGroot, Feb. 2003 - 2003-0018 A&B
Fd. Ok by K. DeGroot, 8/2005 - M146-27

Douglas Co. Surveyors Office - John Pike - Stephen J. Flauser -
2/6/2008 - C.S. File 67/25-12

FD. 1½" IP & all accessories OK as per July 2001 M. Smalley
renewal.