TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #55 dated March, 1855 (DCSO Records, Volume 10 Page 4372)

Set ¼ sec. post, from which
A B.Oak 20" dia., bears N.20°W., 90 lks. dist.
A B.Oak 12" dia., bears S.30°W., 208 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy; R Irving; J. Fee; - June 1955 - C.S. 46/154 (PG 36 of scan), M 1-34

Original BTs not fd. Position of corner located by proportional measurements.
Set 1" I. P. with brass cap mkd. County Surveyors Office 1955
¼ Corner $\frac{7}{18}$ T 26 S R 3 W
New BTs - Blaze & scribe 12" W.Oak N.69°W., 65.8 ft. ¼ S7 CSBT
Blaze & scribe 12" W.Oak S.11½°W., 77.0 ft. ¼ S18 CS BT.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack Heritage - Feb. 1966 - C.S. File 54/7-55

Found - Brass cap at corner by Byron, 1955.
12" W.Oak N.69°W., 65.8 ft. burned, no scribe. Stump
12" W.Oak S.11½°W., 77.0 ft. shows "18 CS" reverse. (Stump)
New BT - 6" D.Fir S.62°W., 40.0 ft. mkd. ¼ S18 CS BT.
No trees to North.
Corner lies 30 ft. North of small creek, flowing SE.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 10/25/2007 - C.S. File 67/24-36

Found - 2½" dia., DCSO brass cap on 1¼" OD IP properly mkd., projects 9" above ground. Firmly set.
No sign of any previous accessories or root holes detected. 30 ft. call to seasonal creek fits reasonably well.
New - 14" dia., ash double blazed & scribed "¼ S 18 CS BT" bears S.84¼°W., 37.3 ft.
Double trunk B.Oak, Westerly trunk is 17" dia., & is double blazed & scribed "¼ S18 CS BT" bears S.8½°W., 140.6 ft.
"X" on top of 18"x18" exposed surface of buried boulder, 3" tall "X" bears N.37½°W., 66.7 ft. Buried spike nail on easterly edge of boulder.