

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION ¼ Cor. Sec. 6; & Sec. 31, T25-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 9 Page 3663)

Set Qr. sec. post, from which
A Cedar 22" dia., bears S.5°W., 150 lks. dist.
A B.Oak 6" dia., bears N.10°E., 21 lks. dist.

Ben B. Irving, Deputy, Co. Surveyor - Wit: E. Russell
W.C. Chapman (No reference found) Dec. 26, 1922

Identified location from original BTs. Drove 1¼" Iron pipe.
for corner, from which:
16" Fir bears S.5°54'E., 144 ft.
18" Fir bears N.31°33'E., 66 ft.

GLO Dependent Resurvey by Norman D. Price, Under Special
Instructions dated April 5, 1940 (DCSO records, Volume 27
Page 11501)

Proportional measurement.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground for
¼ sec. cor., with brass cap mkd. $\frac{1}{4} \frac{S31}{S6}$
1943

from which
A Fir 20" dia., bears N.26°E., 11 lks. dist., mkd. ¼
S31 BT.
A Fir 20" dia., bears S.61°W., 6 lks. dist., mkd. ¼
S6 BT.

Milo Godfrey and Crew - July 31, 1962 - C.S. File 49/102-8

Found - Iron pipe with brass cap mkd: US General Land
Office 1943 $\frac{1}{4} \frac{S31}{S6}$
Fir stump 21", S.61°W., 4 ft. scribing still
visible in partly closed scar "S6 BT".
20" Fir stump N.26°E., 7.3 ft. scribing visible
in open scar "¼ S31 BT".
New BTs - 11" D.Fir S.11°E., 12.8 ft. mkd. "¼ S6 CS BT".
13" D.Fir N.4°W., 17.4 ft. mkd. "¼ S31 CS BT".
Corner is 70 ft. North of a fence line running E & W.

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION ¼ Cor. Sec. 6; & Sec. 31 of T25-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Doug. Co. Surveyors Off. - Vernon Tracy; Mike Stone; J. Layne
Feb. 1, 1966 - C.S. File 54/7-37

Found - Brass cap set by GLO in 1943.
Fir stumps referred to by Godfrey.
11" D.Fir S.11°E., 12.8 ft. Alive. Face pitched
over. We do not disturb.
13" D.Fir N.4°W., 17.4 ft. Dead. Burned, partial
scribe visible.

New BT - 8" D.Fir N.86°W., 51.1 ft. mkd. "¼ S31 CS BT"
Corner is 70 ft. North of E-W fence and 20 ft. East of Creek,
course South.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 10/8/2007 - C.S. File 67/24-30

Found - 2½" dia., brass cap properly marked on 1" O.D. iron
pipe firmly set projects 8" above ground.
1¼" dia., iron pipe looked for & not fd. (1922
corner)
Root hole with bits of burnt bark fits well with
record (N.26°E., 7.3 ft.) 1943 BT
Root hole depression fits well to SE (Rec. S.11°E.,
12.8 ft.)

No sign of any other accessories noted.
New - 3"x3" "X" chiseled on to 2 ft x 2 ft x 3 ft tall
pointed stone, bears N.18°W., 56.6 ft.
Piston butt maple, 11" dia., double blazed & scribed
"¼ S6 CS BT" center of root crown bears
S.14°W., 138.8 ft.
3"x3" "X" chiseled onto 8 ft. x 2 ft. x 2½ ft. tall
stone, "X" is approx 1.2 ft. below highest
point on stone, bears N.25°E., 230.4 ft.
Double trunk maple, westerly trunk is 24" dia.,
burnt, hollow, mkd "X BT" on high single blaze
center of root crown bears S.80½°E., 197.9 ft.

Nearby survey monument sign bears East 1 ft.
Note - East-West fence to south now removed. Corner lies in
area that appears to be periodically burned.
Compass decl. 16¼°E.