

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. 31 & 32; 5 & 6 of T 27-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 10 Page 4350)

Set post, cor. to secs. 31, 32, 5 and 6, from which
A W.Oak 8" dia., bears N.23°W., 55 lks. dist.
A B.Oak 15" dia., bears N.18°E., 79 lks. dist.
A B.Oak 18" dia., bears S.60°E., 22 lks. dist.
A B.Oak 5" dia., bears S.61°W., 104 lks. dist.

A.R. Evans - R.G. Irving - Oct. 19, 1950 - C.S. File 44/61

Found BT alive and standing, 8" W.Oak now 15" N.23°W., 55 lks.
Set - $\frac{3}{4}$ " Iron rod for corner.
Blazed and scribed new BTs:
20" Fir S.32°W., 30.9 ft. mkd. T27S R3W S6 CS BT.
30" B.Oak N.45°W., 65.0 ft. mkd. T26S R3W S31.
No other trees available.

BLM survey, Harold D. Corbin - Under special instructions
dated May 3, 1957, Survey Aug/Nov 1958 (DCSO records, Vol.
29 Page 12440)

Found point for cor. perpetuated with an iron post, $\frac{3}{4}$ " dia.,
firmly set, 1" above ground at record bearing and distance
from the only remaining original bearing tree:

A W.Oak stump 15" dia., bears N.23°W., 55 lks. dist.,
with illegible scribe marks on a partially healed
blaze.

and locally established bearing trees:

A Fir stump 20" dia., bears S.32°W., 47 lks. dist.

A W.Oak stump 30" dia., bears N.45°W., 98½ lks. dist.,
with scribe marks R3W S31 CS BT visible on an
opened blaze.

At the corner point, set an iron post 28" long 2½" dia., 27"
in the ground, with brass cap mkd.

T 26 S R 3 W

S 31 | S 32

S 6 | S 5

T 27 S

1958

A Fir 26" dia., bears N.61¾°E., 1202 lks. dist. mkd.
T26S R3W S32 BT.

(Cont. Next Page)

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. 31 & 32; 5 & 6 of T 27-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>A Fir 11" dia., bears S.11¼°E., 128 lks. dist., mkd. T27S R3W S5 BT.</p> <p>A Fir 6" dia., bears S.28°W., 230 lks. dist., mkd. T27S R3W S6 BT.</p> <p>A Fir 6" dia., bears N.52¼°W., 170 lks. dist., mkd. T26S R3W S31 BT.</p> <p>Deposit local corner material alongside iron post.</p>	
<p>Fd. OK, Doug. County Surveyors Office - 1957 - C.S. 49/14-10 Found OK by D. Edwards, May 2001 - M138-18 and CS 65/34-8</p>	
<p>Douglas Co. Surveyors Office - John Pike - Stephen J. Flauser - 2/14/2008 - C.S. File 67/25-14</p> <p>-----</p> <p>Found - 3¼" dia., (BLM) brass cap markings becoming indistinct, is fd 3" below ground. 11" now 32" dia., x 3 ft. tall D.Fir stump (cut on angle) healed low blaze visible bears S.11¼°E., 84.5 ft. (agrees w/rec) 1958 BT</p> <p>6" now 36" dia., x 1 ft. tall D.Fir stump, healed low blaze visible bears S.28°W., 150.6 ft. (Rec. S.28°W., 151.8 ft. 1958 BT.</p> <p>6" now 14" dia., x 6" tall rotten D.Fir stump, part of lower healed blaze visible bears N.52¼°W., 112.2 ft. (agrees w/rec) 1958 BT.</p> <p>26" now 43" dia., D.Fir fully healed single blaze visible bears N.61¼°E., 793.3 ft. - checked by traverse, no longer direct line of sight - (agrees w/rec) 1958 BT</p> <p>New - 14" dia., I.Cedar, double blazed & scribed "T27S R3W S6 CS BT" bears S.21½°W., 39.3 ft. Double trunk madrone, northerly trunk is 18" dia., and is scribed "T26S R3W S31 CS BT" center of root crown bears N.62°W., 16.4 ft. N.45°W., 7 ft. to old fence corner with decapitated fences running West & North.</p> <p>Note - Corner lies 8 ft. east from center of graveled rd. older clearcut to NW. New clearcut in all other quadrants with isolated timber patches near ridge top. Compass decl. 16¼°E.</p>	
<p>2</p>	