TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #55 dated March, 1855 (DCSO Records, Volume 10 Page 4365)

Set ¼ sec. post, from which
A B.Oak 18" dia., bears N.35°E., 33 lks. dist.
A B.Oak 8" dia., bears N.89°W., 47 lks. dist.

J.W. Cole, Deputy; L.H. Smick asst.; Witnesses, Seth Mathews; Floyd Watson - June 6, 1921 - Volume 3 Page 95

Renewed this corner from the decaying remains of original tree. Set at hole where tree stood and ran S.35°W., 22 ft. Set a Cedar post, also a rock 6 x 10 x 20" from which hole where other BT stood bears N.89°W., 31 ft.
Marked new tree:
A B.Oak 24" dia., S.33°E., 83.3 ft.
Chimney of Forest Blakley house, S.62°40'W.

Doug. County Surveyors Office - Milo E. Godfrey, Deputy; Wm. Stoffel; Mike Stone - December 1963 - C.S. File 53/34-6

Found - Rock mkd. "¼S" on E. face, also cedar stake rotted off & lying on ground beside rock.
28" B.Oak S.33°E., 83.3 ft., has been opened previously & face badly rotted. Portion of reverse scribing on overgrowth.
Stump hole & rotted remnants of Oak stump, N.35°E., 21.8 ft. (orig. BT)
No trace of orig. NW BT.
Set brass cap alongside rock at cor. mkd: County Surveyor's Office, 1963 T26S R3W ¼ 31|S32
New BTs - 16" D.Fir S.70°E., 33.8 ft. mkd. ¼ S32 CS BT.
12" D.Fir N.49°E., 26.8 ft. mkd. ¼ S32 CS BT.
No trees available W. of line. Cor. lies 4.6 ft. East of N-S fence line.

Fd. OK by D. Edwards, June 2001 - M138-27
Found OK by K. DeGroot, June 2002 - 2002-0034 A & B
Fd. BC & 2 BTs by K. Hoffine, 7/2007 - M153-77