

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #55 dated March, 1855  
(DCSO Records, Volume 10 Page 4367)

-----  
Set post cor. to secs. 19, 20, 29 and 30, around which a mound  
was raised as per instructions.  
Observed house N.42°W., 450 lks. dist.

-----  
Bureau of Land Management survey by C. Albert White; Donald  
Beck; Patrick Reynolds - Group #'s 242, 491, 527 - Survey  
June 1962 - August 1963 (DCSO records, Volume 32 Pg. 13391)

-----  
Corner determined at record bearing and distance from the site  
of the original cabin on Donation Land Claim #44. The cabin  
site is indicated by J.C. Livingston, as per his affidavit  
dated August 24, 1963, attached. Nothing remains of the  
cabin, but the site bears N.42°W., 450 lks. dist.

At the corner point,

Set an iron pipe, 3/4" dia., 18" long, the top 6" below the  
surface of the ground in open field, from which

An Iron post 28" long, 2 1/2" dia., set 24" in the ground  
for a reference monument, bears S.81°15'W., 277 lks.  
dist. with brass cap mkd. T26S R3W S30 RM 1963, and  
an arrow pointing to the corner. Reference monument  
falls in a N. and S. fence row and on E. edge of  
dirt road.

-----  
Found OK in August 1994 by DeGroot - M120-65.

-----  
Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 11/1/2000 - C.S. File 66/18-5

-----  
Found - 1963 BLM brass cap/iron pipe protrudes 6" above  
ground 2 ft. East of a N-S fence line, mkd:

U.S. CADASTRAL SURVEY

RM

(Arrow pointing approx. N.81°E.)

T26S R3W

1963

BUREAU OF LAND MANAGEMENT

1963 3/4" I.D. iron pipe is found 6" below ground in  
open field at corner position determined by BLM  
in 1963.

1963 RM brass cap iron pipe bears S.81 1/4°W., 182.82  
ft. (agrees w/rec.) from corner.

Dec. 17 3/4°E.

New - Bearings & distances taken from corner 3/4" I.R. 6"  
below ground. continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A rectangular cupola like structure on top of a 3 car log garage, bears N.21½°W. No distance taken.  
12" dia., apple double blazed & scribed "X BT" bears S.19°E., 471.2 ft.  
13" dia., Maple single blazed & scribed "T26S R3W S29 CS BT" bears S.2½°E., 617.7 ft.  
2½ I.P., 5 ft. high permanent irrigation sprinkler with a concrete base. The most Northerly sprinkler in middle row bears N.15½°E., 63.7 ft.