

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #55 dated March, 1855
(DCSO Records, Volume 10 Page 4371)

Set post cor. to secs. 7, 8, 17 and 18, around which a mound
was raised as per instructions.

Doug. County Surveyors Office - James W. Byron, Deputy; R.
Irving; J. Fee - June 1955 - C.S. File 46/154 (pg 47 of scan)

Location of corner determined by double proportion.
Set brass cap 2" under surface, mkd. CS 1955 $\frac{7}{18} \frac{8}{17}$ T26S R3W
New BTs - Bark and blaze 40" R.Fir N.35°W., 173.6 ft. "S7 T26S
R3W CS BT.
Bark and blaze 50" triple Cedar S.22½°W., 173.3 ft.
"S18 CS BT.
No suitable trees in NE or SE quadrants.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 10/25/2007 - C.S. File 67/24-39

Found ok except now triple trunk cedar has only most southerly
trunk remaining. Bearing & dist. still check well to center of
root crown.