

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 & 8

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Original - Addison R. Flint, Contract #55 dated March, 1855
(DCSO Records, Volume 10 Pages 4372-73)

Set post cor. to secs. 5, 6, 7 and 8, from which
A Red Fir 3" dia., bears S.71°E., 10 lks. dist.
A Dogwood 3" dia., bears S.75°W., 38 lks. dist.
A Maple 3" dia., bears N.27°W., 49 lks. dist.
A B.Oak 3" dia., bears N.35°E., 21 lks. dist.

A. Boyer - H. Northcraft; P.C. Armstrong; D.C. Cooper -
Dec. 18, 1949 - C.S. File 40/237B, M 16-76

Found original scribed corner stake and BT to NW, scribe marks
still distinct. Found also Maple BT to NW, partly decayed.
Set a 4" x 4" cedar post here, properly scribed for corner.
New BTs - 14" Fir S.29°30'W., 20.3 ft. mkd. S7 1581 BT.
16" Fir N.47°W., 16.4 ft. mkd. S6 1581 BT.
16" Fir S.47°10'E., 46.4 ft. mkd. S8 1581 BT.
14" Fir N.78°45'E., 43.5 ft. mkd. S5 1581 BT.
The above distances to centers of trees.
Corner in flat, about 30 ft. East of N & S. fence.

Doug. County Surveyors Office - James W. Byron, Deputy - For:
G.C. Finlay - May 26, 1955, C.S. File 46/154 (PG 10 of scan)

Found - 4 x 4 stake & stumps of all BTs as set by Boyer.
Set 1" I.P. with brass cap mkd. County Surveyors Office 1955
Cor. $\begin{matrix} 6 & 5 \\ 7 & 8 \end{matrix}$ T 26 S R 3 W

from which
8" Cedar S.29°E., 81.4 ft. blazed & scribed S8 CS BT.
Mt. Scott Lookout bears N.25½°E.
8" Laurel S.20½°W., 157.8 ft. blazed & scribed S7 CSBT.
18" R.Fir N.24°W., 221.0 ft. blazed & scribed S6 CSBT.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause
- 10/29/2007 - C.S. File 67/24-40

Looked for not found.
Derived coordinates from topo quad map. Position falls in
pasture of burnt & cleared stumps N-S fence still intact.