TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 32; & 5 of T27-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 10 Page 4350)

Set ¼ sec. post, from which
A B.Oak 7" dia., bears N.49°W., 37 lks. dist.
A W.Oak 7" dia., bears S.27°E., 89 lks. dist.

Ben B. Irving; A.R. Evans. N.E. Richardson - 10/1950 -CS 44/61

Set by proportionate measurement.
Set 1" I.P. with brass cap marked County Surveyors Office, T26S R3W ¼ S32 T27S R3W ¼ S5.
Blazed and scribed 2 BTs:
8" W.Oak N.60°W., 19.1 ft.
8" W.Oak S.53°E., 53.6 ft.

Douglas Co. Surveyors Office - V.R. Tracy - 2/1966 - C.S. 54/7-26A

Searched for, not found. Corner falls in cat cleared field.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 5/15/2001 - C.S. File 66/21-18

Found - 1950 DCSO bent BC/IP protrudes 3" above ground bent 5" NW of plumb position referenced BC/IP removed and straightened flanges in good shape IP measures 36" long, mkd: COUNTY SURVEYOR
COR
¼ T 26 R 3
S 32
S 5
T 27 R 3
OFFICE

No BTs found, possible root hole of 1950 NW BT (Rec. N.60°W., 19.1 ft.)

Set - Brass cap iron pipe returned to plumb position, protrudes 3" above ground.
13" dia., D.Fir double blazed & scribed "¼ S5 CS BT" bears S.21°E., 33.7 ft.
6" dia., D.Fir double blazed & scribed "¼ S5 CS BT" bears S.5°W., 42,3 ft.
7" dia., D.Fir double blazed & scribed "¼ S32 CS BT" bears N.13°E., 67.9 ft.
7" dia., W.Oak double blazed & scribed "¼ S32 CS BT" bears N.29°W., 64.0 ft.(Compass decl. 17 3/4°E)

CONT.

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 32; & 5 of T27-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Fd. BC & 4 BTs by K. Hoffine, 7/2007 - M153-77