

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #55 dated March, 1855
(DCSO Records, Volume 10 Page 4366)

Set ¼ sec. post, from which
 A W.Oak 6" dia., bears N.58°E., 346 lks. dist.
 An Ash 2" dia., bears S.53°E., 393 lks. dist.

Don E. Garrett, For: R.A. Standley - March 1970 - M 33-72

Corner set by proportionate measurement.
Set - Brass cap and established bearing trees:
 5" Ash, in Ash clump N.7°W., 7.0 ft. scribed "¼
 S29 BT".
 12" W.Oak S.70°E., 178.9 ft. scribed "¼ S32 BT".

Doug. County Surveyors Office - Larry E. Monrean, Deputy;
Randall Smith; Stephen Flause - Dec. 27, 1984 - C.S. 62/21-19

Found - A disk on an I.P. protrudes 15" above a 1 ft. dia.
 mound of stone per Garrett.
 5" now 6" dia. Ash with a partially healed double
 blaze, scribing visible "¼ S29 BT" bears
 N.7°W., 7.0 ft.
 12" now 14" W.Oak with a partially healed double
 blaze illegible scribing visible, bears
 S.70°E., 178.9 ft.
New BTs - 6" Ash double blazed & scribed "¼ S23 CSBT" bears
 S.7½°E., 29.5 ft. (Notes say 23, probably is
 meant to be 32) (V.L. 6/5/92)
 4" Ash double blazed & scribed "X BT" bears N.65°W.,
 17.2 ft.
Corner lies near the east edge of a swampy ash grove in an
E-W fence line.

Fd. OK by D. Edwards, June 2001 - M138-27
Fd. BC & 4 BTs by K. Hoffine, 7/2007 - M153-77

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause -
2/12/2008 - C.S. File 67/25-12

Fd. BC/IP & al accessories as per Dec. 1984 DCSO.
Ren. note: Partial healed blaze on 6" Ash (Rec. S.7½°E., 29.5
ft.) reveals it is indeed scribed "¼ S32 CS BT"