

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>Original - Addison R. Flint, Under Contract #55, dated March 1855 (DCSO records Volume 10 Pages 4358-59) ----- Set ¼ sec. post, from which     A B.Oak 8" dia., bears N.69°W., 596 lks. dist.     A Pine 36" dia., bears S.78°E., 226 lks. dist.</p>
<p>J.W. Cole, Deputy - L.H. Smick; Floyd Watson; Set Mathews For: Lexington Invest. Co. (Walter Hamilton) June 6, 1921 Volume 3 Page 95 - Field Book 51 Page 32 ----- Renewed from original BTs, both alive and standing. Set a Rock, 8 x 8 x 24" marked ¼S CS , from which     48" Pine S.78°E., 149.2 ft.     B.Oak 14", bearing scars, N.70°W., 398.2 ft. Erected mound of rock.</p>
<p>Doug. County Surveyors Office - Vernon Tracy; Mike Stone; J. Layne; Jack Heritage - Feb. 1966 C.S. File 54/7-27 ----- Found - Basalt stone 8 x 9 x 24", firmly set in mound of stone.     Orig. 36" now 60" Pine S.78°E., 149.2 ft., burned snag, open, badly rotted, no scribe found.     Possibly bark scribed.     No trace of B.Oak to NW. Set Brass cap in place of stone 12" in ground &amp; build mound of stone around pipe &amp; mkd: County Surveyor Office, 1966     T26S R3W ¼ S32 S33 New BTs - 10" Cedar S.47°W., 29.1 ft. mkd: ¼ S32 CS BT.     12" Pine S.34°E., 6.8 ft. mkd: ¼ S33 CS BT.</p>
<p>Found OK, D. Bentz, January 1989, M 107-46  Fd. Ok by Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/29/1999 - C.S. File 66/12-43  Fd. OK by D. Edwards, June 2001 - M138-27 Fd. BC &amp; 2 BTs by K. Hoffine, 7/2007 - M153-77</p>
<p>Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 1/8/2008 - C.S. File 67/25-5 ----- OK - Fd. 2 live BTs as per 1966 DCSO renewal.</p>
<p> </p>