

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #55, dated March 1855 (DCSO records Volume 10 Page 4359)

Set post, cor. to secs. 28, 29, 32 and 33, from which
A B.Oak 18" dia., bears N.12°E., 390 lks. dist.
A B.Oak 24" dia., bears N.18°W. 303 lks. dist.
A W.Oak 23" dia., bears S.37°W., 356 lks. dist.
A W.Oak 10" dia., bears S.65°E., 390 lks. dist.

Floyd Frear, Surveyor - Jack Bathrick; Durwood Owens
Feb. 21, 1949 (No source record found - Possibly during
Frear's County Road work)

Set ½" x 1¾" x 36" Iron bar and mound of rock. Found O.B.T.
with marks gone, which bears S.37°W., 235 ft. Remark.
Also mark:
2 ft. forked W.Oak bears S.44½°W., 130 ft.
10" W.Oak bearing S.7°E., 129.8 ft.

Bureau of Land Management Dependent Resurvey by White; Beck
and Reynolds Group #'s 242; 491; 527 Survey June 1962-August
1963 (DCSO records, Volume 32 Page 13390-91)

Corner determined at record bearing and distance from one
original bearing tree:

A W.Oak 39" dia., bears S.37°W., 356 lks. dist., with
opened and rotted blaze.
and bearing trees marked by Floyd Frear, County Engineer in
1949:

A W.Oak 15" dia., bears S.7½°E., 188 lks. dist. with a
healed blaze.

A W.Oak 29" dia., bears S.46°W., 193 lks. dist., with
a healed blaze.

At the Corner point, bury an iron post, 28" long, 2½" dia.,
the top 18" below the surface of the ground, with brass cap
marked:

T 26 S R 3 W
S 29 | S 28
S 32 | S 33

from which

A W.Oak 10" dia., bears N.17¼°E., 349 lks. dist.
mkd. T26S R3W S28 BT.

A W.Oak 30" dia., bears N.65¼°W., 327 lks. dist.,
mkd. T26S R3W S29 BT.

The Corner falls in open field.

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Doug. County Surveyors Office - R.B. Kimberling; P.L. Earle
June 2, 1977 - C.S. File 59/34-27

Found - 2½" I.P. with a 3¼" Brass cap below ground level.
Cap stamped with R2W (wrong range stamped)
39" W.Oak bears S.38½°W., (Rec. S.37°W) 235.0 ft.
with open rotted out blaze.
An Orig. 10" now 19" W.Oak bears S.6°E., 124.1 ft.
(Rec. S.7°E.) 129.8 ft., 1949) with well healed
blaze.
An orig. 2 ft. now 30" W.Oak bears S.47½°W., 127.8
ft. (Rec. S.44½°W., 130.0 ft., 1949) with well
healed blaze. Tree is four trunked, measured
3 ft. above the ground.
An orig. 10" now 15" B.Oak bears N.18½°E., 231.1 ft.
(Rec. W.Oak N.17¼°E., 230.3 ft.) with well
healed blaze.
An orig. 30" now 40" forked B.Oak bears N.64°W.,
216.0 ft. (Rec. W.Oak N.65¼°W., 215.8 ft.) with
well healed blaze. Tree measured below fork.
No new monument set. Slashed out incorrect 2 on brass cap,
stamped 3 above.
Note: Found ½" x 1¾" Iron bar in 24" deep hole ± 4 ft.
north of brass cap. Watson C. Talcott stated that
he, an interested nearby resident, had found said
iron bar in that location and had dug it out trying
to find brass cap. Drove iron bar at North edge of
brass cap, flush with top. Set steel fence post
with witness sign attached directly above brass cap.

Found OK, Dec. 13, 1982, J. Powell for Doug. County Surveyors
Office - C.S. File 62/1-33 (39" W.Oak, S.38½°W., 235.0 ft. is
to be removed by construction.)

Fd. BC & 4 BTs, Ron Quimby, 5/2007 - M153-2