

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #55, dated March 1855 (DCSO records Volume 10 Page 4360)

Set post, cor. to secs. 20, 21, 28 and 29, from which
A B.Oak 13" dia., bears N.37°W., 22 lks. dist.
A B.Oak 20" dia., bears N.38°E., 104 lks. dist.
A B.Oak 10" dia., bears S.55°E., 66 lks. dist.
A W.Oak 16" dia., bears S.8°W., 47 lks. dist.

BLM resurvey by White; Beck and Reynolds -Group #'s 242; 491 and 527 - Survey June 1962-Aug. 1963 (DCSO records Volume 32 Page 13390)

Point for the cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an Iron post 28" long 2½" dia., 24" in the ground, with brass cap mkd:

T 26 S R 3 W
S 20 | S 21
S 29 | S 28
1963

from which
A Fir 12" dia. bears N.25¼°E. 45 lks. mkd T26S R3W S21 BT
A B.Oak 14" dia., bears S.26¼°E., 31 lks., mkd. T26S R3W S28 BT.
A Fir 8" dia. bears S.56½°W. 37 lks. mkd. T26S R3W S29 BT
A Fir 15" dia., bears N.80¾°W., 50 lks., mkd. T26S R3W S20 BT.

Ronald Quimby - For: Neil Talcott - May 2007 - M 153-2

Found - Brass cap
29" Fir bears N.25°15'W., 29.7'
New - 21" Fir bears S.24°E., 25.0', scribed "S28 BT"
24" Fir bears S.49°W., 19.9', scribed "S29 BT"
16" Fir bears N.64°W., 38.9', scribed "S20 BT"