

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 8, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #55, dated March 1855 (DCSO records Volume 10 Page 4362)

To post cor. of secs. 8, 9, 16 & 17, around which a mound was raised with stones, as per instructions.

GL0 Dependent Resurvey by Fred Mensch, Under Special Instructions dated July 14, 1924 (DCSO records, Vol. 11 Page 4401)

The cor. of secs. 8, 9, 16 and 17, is now marked only by the old mound of stones, originally built around the post. In the center of the old mound -
Set an Iron post, 3 ft. long, 2" dia., 27" in the ground, for cor., with brass cap mkd:

T	26	S	R	3	W
	S	8		S	9
	S	17		S	16
				1924	

from which

A W.Oak 10" dia., bears N.71°E., 82 lks. dist., mkd.
T26S R3W S9 BT.

A double W.Oak 12" dia., bears S.79°E., 121 lks. dist.
mkd. T26S R3W S16 BT.

A W. Oak 12" dia., bears S.33°W., 35 lks. dist.,
mkd. T26S R3W S17 BT.

A W.Oak 18" dia., bears N.82°W., 132 lks. dist., mkd.
T26S R3W S8 BT.

Doug. County Surveyors Office - H.L. Eppstein - Wit: W.S. Crear; F.L. Perry - Juen 15, 1928 - Vol. 3 Page 282
C.S. File 7/46

Corner set by Gov't Surveyor, standard pipe for corner with the following witness trees:

W.Oak 12" S.35°30'W., 23 lks.

W.Oak 12" N.72°E., 54 lks.

W.Oak 16" S.79°30'E., 120 lks.

W.Oak 16" N.79°30'W., 131 lks.

Doug. County Surveyors Office - James Byron, Deputy
May 1955 - C.S. File 46/154 (PG 18 of scan)

(Cont. Next Page)

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Found - 1924 brass cap at corner.
The NW BT which checks for bearing & distance, is the only BT left. The other BTs have been cut. 7 stumps rotted.
The NW Bt now 24" shows good blazes, I do not cut out.

Blaze and Scribe:
8" W.Oak S.62°E., 85.0 ft. "S16 CS BT"
10" W.Oak N.72°E., 53.8 ft. "S9 CS BT"
10" Cedar S.7½°W., 31.9 ft. "S17 CS BT"

Fd. Ok by R. Quimby 5/2006 - M151-11