

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 300520

PRIMARY CORNER DESCRIPTION So. 1/16 Cor. of Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO Dependent Resurvey by Fred Mensch, Under Special Instructions dated July 14, 1924 (DCSO records, Volume 11 Page 4409)

Proportional measurement

Set an Iron post 3 ft. long, 1" dia., 27" in the ground, for S 1/16 sec.cor., with brass cap marked:

S $\frac{1}{16}$
S 8|S 9
1924

from which

A Cedar 28" dia., bears N.14°E., 48 lks. dist. mkd.
S 1/16 S9 BT.

A B.Oak 10" dia., bears N.82¾°W., 183 lks. dist., mkd.
S 1/16 S8 BT.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone;
Jerry Layne - Jan. 1966 - C.S. File 54/7-12

Found - GLO brass cap 1924 mkd. "S 1/16 S8|S9"
10" now 29" B.Oak N.83¾°W., 120.8 ft., shows
faint scar, we do not open.
NE BT down and badly burned.

New BT - 17" B.Oak in clump of three, N.88°E., 32.9 ft. mkd.
"S 1/16 S9 CS BT".

This corner lies near bottom of SW slope 136 ft. North of
fence, course S.70°W., and N.70°E.