

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Under Contract #55, dated March 1855 (DCSO records Volume 10 Page 4363)

-----  
Set 1/4 sec. post, from which  
    A B.Oak 18" dia., bears S.15°W., 216 lks. dist.  
    A B.Oak 25" dia., bears N.45°E., 78 lks. dist.

-----  
J.W. Cole, Co. Surveyor - Wit: J.B. Davis; O.L. Shockley;  
W.W. Bogard; McDonald - Jan. 1, 1924 - Field Book 52 Pg. 15

-----  
Found Fir stake not marked, set by O. Thiel which checks with large B.Oak N.45°E., 51.5 ft. standing, dead, scribe marks visible. Other BT entirely gone. I marked:  
    A Fir 18" S.28°30'W., 12.0 ft.  
    A Fir 28" S.29°E., 30.5 ft.

-----  
GLO Dependent Resurvey by Fred Mensch, Under Special Instructions dated July 14, 1924 (DCSO records, Vol. 11 Pg. 4409)

-----  
The point for the 1/4 sec. cor., determined by reference to the original bearing tree, a B.Oak 36" dia., which bears N.45°E., 78 lks. dist., old blaze partly opened, marks visible.  
At the exact cor. point  
Set an Iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap mkd:

1/4  
S 8 | S 9  
1924

from which  
    A Fir 30" dia., bears S.40°E., 48 lks. dist., mkd.  
        1/4 S9 BT.  
    A Fir 20" dia., bears S.28°W., 20 lks. dist., mkd.  
        1/4 S8 BT.

No trace is found of the old bearing tree in Sec. 8.

-----  
Doug. County Surveyors Office - Vernon Tracy; Mike Stone;  
Jerry Layne - Jan. 1966 - C.S. File 54/7-21

-----  
Found - 1924 GLO brass cap, bent over & stump holes at proper bearing & distance for BTs. recorded in 1924 resurvey.

(Cont. Next Page)

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 and 9

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Found no evidence of corner by Cole.  
Reset Brass Cap.  
Since the closest trees are approx. 600 to 800 ft. off, we use most southerly Pole of 3 wire transmission line as bearing object.  
Pole bears N.32°W., 199.5 ft. Put yellow line tag on pole facing corner.