

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33 of T25-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint Under Contract #56 dated March 1, 1855 (DCSO records Volume 9 Page 3663)

Set post cor. to Secs. 32, 33, 4 and 5, from which
A Red Fir 20" dia. bears S.55°E., 5 lks. dist.
A Red Fir 40" dia. bears N.25°E., 24 lks. dist.
A Red Fir 14" dia. bears S.63°W., 8 lks. dist.
A Red Fir 12" dia. bears N.2°W., 30 lks. dist.

Ben B. Irving, Deputy Co. Surveyor - For: Brown & Tipton
Wit: J.A. Irving; Joseph Brown; Jeff Palouse - April 26, 1930 - C.S. File 37/21

Location identified from 4 original BTs as recorded in Gov't field notes. One BT now down and badly rotted. Most of figures scaled off bark of tree in Sec. 4.
Blazed and scribed an 8" yew N.30°W., 28 lks. T25S R3W S32 CS BT. and remarked in bark, orig. BT in Sec. 4

GL0 Dependent Resurvey by Norman D. Price - Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11503)

The original cor. of secs. 4, 5, 32 and 33, the locus of which has been perpetuated by a county surveyor's cedar stake 3 ft. long 4" square, firmly set, mkd. CS T25S R3W S33 on NE., T26S S4 on SE., S5 on SW., and S32 on NW. face. At point for corner, Set an iron post 3 ft. long 2" dia. 28" in the ground, with the county surveyor's marked stake deposited at the base, for corner, with brass cap marked:

T25S R3W

S32|S33

S5|S4

1943

from which

- A Fir 50" dia. bears N.25°E., 24 lks. dist., marked on bark T25S R3W S33 BT. (Old BT)
- A Fir 34" dia., dead and down, bears S.63°W., 8 lks. dist., with partial scribe marks visible on old bark blaze. (Old BT)
- A Fir 40" dia. bears S.55°E., dead and down, 5 lks. dist. mkd. on bark T26S R3W S4 BT. (Old BT)
- A Fir 32" dia., bears N.2°W., 30 lks. dist., an old bearing tree which has fallen and only part of the old bark is visible.
- A Yew 7" dia. bears N.20°W., 27 lks. dist. mkd. T25S R3W S32 CS BT. (Co. Surveyors BT)

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33 of T25-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Yew 8" dia. bears N.37½°E., 54 lks. dist., mkd.
T25S R3W S33 BT. (New BT)
A Fir 50" dia. bears S.76°E., 73 lks. dist., mkd.
T26S R3W S4 BT. (New BT)
A Yew 8" dia. bears S.62°W., 15 lks. dist., marked
T26S R3W S5 BT. (New BT)

Douglas County Surveyors Office - Vernon Tracy; Mike Stone & J. Layne - Feb. 1, 1966 - C.S. File 54/7-40

Found - 1943 GLO brass cap & BTs in E-W fence 76 ft. W. of fence corner.
Orig. 50" Fir N.25°E., 15.8 ft., bark scribed, alive.
Only rotted remnants left of other orig. BTs.
BTs as recorded by Irving as follows:
7" now 10" yew N.20°W., 17.8 ft., alive, scribe visible on partially healed face.
8" now 13" Yew N.37½°E., 35.6 ft. alive, scribe visible.
50" Fir stump S.76°E., 48.2 ft. scribe visible on face.
8" now 11" Yew S.62°W., 9.9 ft. Alive, scribe visible on partially healed face.
New BT - 18" W.Fir S.22°E., 44.6 ft. mkd. T26S R3W S4 CS BT.

BLM Dependent Resurvey by Rogers, Bedell and Peterson under Group #1386 - Survey June 1987/Sept. 1988 (DCSO records, Volume 48 Page 18475)

Found 1943 brass cap from which an original bearing tree:
A Fir 57" dia. bears N.25°E., 24 lks. dist., with partial bark scribing visible.
and the remains of a bearing tree mkd. by Irving in 1930:
A root hole, bears N.20°W., 27 lks. dist., with a down yew alongside 11" dia. with partially healed rotted blaze.
and the remains of bearing trees mkd. by Price:
A rotted, sawed Yew stump 9" dia. bears N.37¼°E., 54 lks. dist., no marks visible.
A rotted sawed Fir stump 45" dia., bears S.76°E., 73 lks. dist., with fragmentary scribe marks R3W S BT visible on opened blaze.
A root hole bears S.62°W., 15 lks. dist., with a down Yew alongside 12" dia. with partially healed rotted blaze.
and the remains of a bearing tree mkd. by Tracy in 1966:
continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33 of T25-3

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>A sawed Fir stump 18" dia. bears S.24°E., 67½ lks. dist., with healed blaze. and new bearing trees: A Fir 6" dia. bears S.21°E., 29 lks. dist., mkd. T26S R3W S4 BT. A Fir 9" dia. bears S.45¾°W., 60 lks. dist. mkd. T26S R3W S5 BT. A Fir 6" dia. bears N.59°W., 33 lks. dist. mkd. T25S R3W S32 BT.</p>
<p>Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 11/8/2007 - C.S. File 67/24-46 ----- Fd. Ok, 3 live BTs.</p>
<p>Adam DeGroot - For: Dollens & Strader - Dec. 2020 - M178-27 ----- Found - A 2" iron post by Price in 1943, firmly set & projecting 10" above the ground with a 2½" brass cap properly mkd per the record: A 59" D.Fir bears N.25°00'E, 18.8 ft no mks on charred bark. I bark blaze and set nail & brass washer in face at 16.20 ft (N.25°E., 24 lks) OBT A 19" D.Fir bears S.20°45'E., 19.1 ft. w/charred healed blaze (S.21°E., 29 lks) 1988 A 19" D.Fir bears S.45°30'W., 39.1 ft w/charred healed blaze (S.45°45'W., 60 lks) 1988 A 15" D.Fir bears N.59°W., 21.5 ft w/charred blaze (N.59°W., 33 lks) 1988 Note - Corner falls in E-W fence line in low intensity burn area. BTs are alive and trunks charred 15-20 feet high</p>
<p>Douglas Co. Surveyors Office - Crew: Jeff Lorsung- 11/27/2024 - C.S. File 67/59-18 ----- Found - 2½" GLO brass cap (properly mkd) 10" above ground. 59" Fir N.25°E., 18.8 ft. bark blaze nail and brass washer in face at 16.2 ft. 19", 10 ft. high D.Fir stump S.20¾°E., 19.1 ft., charred healed face. 19"x6 ft. high D.Fir stump S.45½°W., 39.1 ft healed, charred healed blaze. 15" D.Fir N.59°W., 21.5 ft. with charred blaze. Metal T-post 2 ft. SE All trees and stumps have tag and side spiked. Note - Corner in E-W fence. Continued next page</p>

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33 of T25-3

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Area burnt 9/2020
Compass decl. 14¼°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 186419.395 E 234083.492