

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 320500

PRIMARY CORNER DESCRIPTION W 1/16 Secs. 9 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey of Subdivision of Sec. 9 by Fred Mensch Under Special Instructions dated July 14, 1924 (DCSO records, Volume 11 Page 4402)

Proportional measurement.

Set an Iron post, 3 ft. long 1" dia., 27" in the ground, for W 1/16 sec. cor. with brass cap mkd. S 9

W $\frac{1}{16}$ S 16
1924

from which

A B.Oak 24" dia., bears N.33°E., 13 lks. dist., mkd.
W 1/16 S 9 BT.

A Fir 8" dia., bears S.41°E., 16 lks. dist., mkd.
W 1/16 S 16 BT.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone;
Jerry Layne - Jan. 1966 - C.S. File 54/7-8

Found - Badly rotted remains of 8" now 15" Fir S.41°E.,
10.6 ft., found "W 1/16 S" scribe & reverse.

No trace of 1924 brass cap nor B.Oak BT to NE.

Set Brass cap at corner mkd: County Surveyor's Office 1966

T26S W 1/16 S 9
R3W S 16

New BTs - 18" D.Fir S.51°E., 17.2 ft. mkd. W 1/16 S16 CS BT.
16" Pine N.24°E., 41.3 ft. mkd. W 1/16 S9 CS BT.

This corner lies approx. 40 ft. S. of N. Umpqua Highway.