

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 320501

PRIMARY CORNER DESCRIPTION Angle Point #2, Power Reserve, S.9

Alias <u>917020</u>	Description <u>AP 2 on W 1/16</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - GLO Segregation survey of Power Reserve, by Fred Mensch, Under Special Instructions dated July 14, 1924 (DCSO records, Volume 11 Page 4417)

-----  
To the point for Angle Point No. 2, on the meridian center subdivisional line bet. the SW ¼ and the SE¼ of the SW¼ sec. 9.

The point for Angle Point #2 falls in the Glide-Hoaglin road, therefore, at a point 11 lks. N.0°07'W.

Set an Iron post, 3 ft. long, 1" dia., 27" in the ground for witness cor. to Angle Point #2, Power Reserve, with brass cap marked:

/  
/  
|A P 2  
|P R  
W C  
1924

from which

A Fir 20" dia., bears S.62°E., 83 lks dist., mkd.

W C A P 2 P R BT.

-----  
Doug. County Surveyors Office - Vernon Tracy; E. Monrean;  
D. Shultz - Dec. 1971 - C.S. File 54/7

(W 1/16 corner for Secs. 9 and 16 bears S.0°07'E., 74.6 ft.)

Found - Old bearing tree mkd. in 1924:

A 20" now 26" Fir, S.62°E., 54.8 ft. Alive, good condition. Shows very good axe scar. Bearing & dist. also matches call dist. & brg. to W. 1/16 S. 9 & 16. Witness cor. falls in N. Umpqua Road.

Set - Drove a R.R. spike at point for witness corner. Due to close proximity of 1/16 cor., no other BTs or ties made.