

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 320520

PRIMARY CORNER DESCRIPTION SW 1/16 Cor. Section 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - GLO survey, subdivision of sec. 9 by Fred Mensch Under Special Instructions dated July 14, 1924 (DCSO records, Volume 11 Page 4415)

-----  
Intersect SW  $\frac{1}{4}$  latitudinal line. At the point of intersection Set an Iron post 3 ft. long 1" dia., 27" in the ground, for SW 1/16 Sec. cor. of sec. 9, with brass cap marked:

SW  $\frac{1}{16}$  S 9  
1924

from which

A Cedar 7" dia., bears S.55°E., 12 lks. dist., mkd.  
S W 1/16 S 9 B T.

A B.Oak 12" dia., bears N.2°W., 25 lks. dist., mkd.  
S W 1/16 S 9 B T.

-----  
Doug. County Surveyors Office - Vernon Tracy; Mike Stone;  
Jerry Layne - Jan. 1966 - C.S. File 54/7-6

Found - 1924 GLO Brass cap.  
7" now 20" Cedar S.5°E., 7.9 ft. recorded S.55°E.  
Open & find reverse "W" scribe.  
Stump hole bears N.2°W., 16.5 ft.

New BTs - 17" D.Fir N.77°W., 36.9 ft. mkd. SW 1/16 S9 CS BT.  
11" W.Oak S.9°E., 48.6 ft. mkd. SW 1/16 S9 CS BT.

This corner lies at fence corner with fences E-W and S.