

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 320540

PRIMARY CORNER DESCRIPTION Center West 1/16 Sec. 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO dependent resurvey by Fred Mensch, Under Special Instructions dated July 4, 1924 (DCSO records, Volume 1 Page 4411)

Set an Iron post, 3 ft. long, 1" dia., 27" in the ground for west center 1/16 sec. cor. of sec. 9, with brass cap marked:

W $\frac{1}{16}$
C _____ C
S 9
1924

from which

An Ash 14" dia., bears N.21°E., 13 lks. dist., mkd.
C W 1/16 S9 BT.
A Fir 9" dia., bears S.52°W., 14 lks. dist., mkd.
C W 1/16 S9 BT.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone;
Jerry Layne - Jan. 1966 - C.S. File 54/7-4

Found - 1924 GLO brass cap.
14" now 26" Ash N.21°E., 8.6 ft., down & dead. Do not open.

SW bearing tree gone.

New BTs - 15" Ash S.56°W., 66.6 ft. mkd. "C W 1/16 S9 CS BT"
12" B.Oak N.85°E., 63.6 ft. mkd. "CW 1/16 S9 CS BT".

This corner lies 25 ft. east of small creek, course SW.