

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 327500

PRIMARY CORNER DESCRIPTION M.C. fractional Sec. 9 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - BLM Dependent Resurvey by Fred Mensch, Under Special Instructions dated July 14, 1924 (DCSO records Volume 11 Page 4403)

Left Bank of North Umpqua River.
Set an Iron post, 3 ft. long, 1" dia., 27" in the ground, for meander cor. of fractional sec. 9 only, with brass cap marked

T 26 S
R 3 W
M C S 9
1924

from which

A Fir 30" dia., bears N.72°E., 46 lks. dist. mkd.
T26S R3W S9 MC BT.
An Ash 8" dia., bears S.89°E., 33 lks. dist, mkd.
T26S R3W S9 MC BT.

Doug. County Surveyors Office - March 18, 1960 - C.S. File 49/48-8

Found - Brass cap at corner mkd as recorded. Also both BTs
The brass cap is near water surface and would probably be washed out by next high water.

I move cap 30 ft. East and add this to cap "moved 30' East CS 1960".

I rescribe both original BTs:

36" R.Fir bears N.4°W., 9.1 ft. scribed S9 WC MC CS BT.
10" Ash bears S.85°W., 8.4 ft. scribed S16 WC MC CS BT.