

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Section 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

M. B. Germond, Deputy For: O. E. Smith, Sept. 1908
Volume 2 Pages 153-154

I drove Rifle Barrel 1¼" dia., 2½ ft. in the ground and set East of it 2", a Red Fir post 4" x 4" x 3 ft., from which
W.Oak 8" dia., bears N.61°07'W., 3.03 lks. dist.
R.Fir 18" dia., bears S.37°48'E., 45.9 lks. dist.
B.Oak 14" dia., bears S.31°15'W., 5.90 lks. dist.

Bureau of Land Management subdivision of Section by White; Beck and Reynolds, Under Group #'s 242; 491 and 527. Survey June 1962-Aug. 1963 (DCSO records, Volume 32 Pages 13398-99)

Point for the center ¼ sec. cor. of sec. 21, at intersection with the E. and W. center line.
Set an Iron Post, 28" long 2½" dia., 24" in the ground, with brass cap mkd. C ¼ S21
1963

from which
A Fir 20" dia., bears S.14°W., 649 lks., mkd. C ¼ S21 BT.
A W.Oak 22" dia. bears N.72¼°W. 252 lks., mkd. C ¼ S21 BT
From this point, a local center ¼ sec. cor. established by M.B. Germond in 1908, bears S.24°00'E., 0.70 chs. dist., at the corner of 2 fences. A barbed wire fence extends W., and a woven and barbed wire fence extends N. Point determined at record distance from Germond's bearing trees:
A rotted Fir stump bears S.37½°E., 459 lks. dist.
An Oak stump shell bears S.31¼°W., 590 lks. dist.
A W.Oak 23" dia., bears N.61°W., 303 lks. dist., with a healed blaze.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 11/2/2000 - C.S. File 66/18-6

Found - 1963 BLM brass cap/iron pipe, protrudes 8" out of ground in a N-S fence line 41 ft. north of a fence corner w/fence line running North & West. 22" now 20" dia., down & rotted oak, no scribing visible root hole bears N.72¼W., 166.3 ft. 1963
No other BTs found.
1" O.D. rifle barrel 6" below ground bears S.24°E 46.2 ft. (agrees w/1963 BLM rec.) Set by DCSO in 1908 for cor.
New - 33" dia., W.Oak double blazed & scribed "C¼ S21 CS BT" bears N.80°W., 188.3 ft.

continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 340340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

7" dia., capped well pipe protruding 13" above ground bears N.65°W., 82.0 ft.
13" dia., D.Fir double blazed & scribed "C¼ S21 CS BT" bears S.21¼°E., 343.0 ft.
7" dia., capped well pipe protrudes 12" above ground bears N.10 3/4°W., 73.5 ft.
Note - Bearings need to be taken away from well casing as they effect bearings.
Dec. 17 3/4°E.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 2/7/2023 - C.S. File 67/55-39

Found - 3¼" BLM brass cap (properly mkd) on 2" ID IP, up 8".
1" O.D. rifle barrel, 6" below ground, bears S.24°E., 46.2 ft. (set by DCS0 in 1908 for cor.)
35" W.Oak N.80°W., 188.3 ft, good scar.
7" capped well pipe projecting 13" bears N.65½°W., 83.9 ft OCRS B&D (Rec. N.65°W., 82.0 ft)
20" D.Fir S.21¼°E., 343.0 fully healed double blaze.
7" capped well pipe projecting 12" bears N.12½°W., 74.0 ft. OCRS B&D (Rec. N10¾°W., 73.5 ft.)
New - 5/8"x30" I.Rod with DCS0 yellow plastic cap, East 10.0 ft.
Note - Area burnt 9/2020
Compass decl. 14½°E.
OCRS Coordinate System Cottage Grove - Canyonville Zone
N 167860.477 E 236909.553