

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Under Contract #55, dated March 1855 (DCSO records Volume 10 Page 4363)

-----  
Set ¼ sec. post, from which  
    A B.Oak 16" dia., bears S.25°E., 310 lks. dist.  
    A B.Oak 15" dia., bears N.58°W., 359 lks. dist.  
This post sets in a small prairie about 1½ chs. wide NW to river.

-----  
M.B. Germond For: Herbert Connine - Sept. 1908 Vol. 2 Pg. 154

-----  
Reset this ¼ corner with durable W.Oak post 4" x 4" x 3 ft., properly marked and note that old BTs are still standing as per government field notes.

-----  
GLO Dependent Resurvey by Fred Mensch, Under Special Instructions dated July 14, 1924 (DCSO Records, Vol. 11 Page 4403)

-----  
The old ¼ sec. cor., which is a sound oak post, set by local surveyor, from which  
    A B.Oak stump 36" dia., bears S.24°E., 318 lks dist. mkd. ¼ S BT.  
    A B.Oak 32" dia., bears N.56½°W., 366 lks. dist., shows blaze scars, not opened.

Alongside the post, which is on fence line,  
Set an Iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor, with brass cap mkd:

¼  $\frac{S\ 9}{S\ 16}$   
1924

from which  
    A Fir 20" dia., bears S.85¼°E., 179 lks dist. mkd. ¼ S 16 BT.  
    A W.Oak 10" dia., bears N.15°W., 35 lks. dist., mkd. ¼ S9 BT.

-----  
Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jerry Layne - Jan. 1966 - C.S. File 54/7-23

-----  
Found - GLO brass cap at 4-way fence cor.

(Cont. Next Page)

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Also found old Oak post.  
20" Fir S.85¼°E., 118.1 ft. cut flush with ground,  
no scribe.  
10" now 16" W.Oak N.15°W., 23.1 ft. shows good scar,  
we do not open.  
New BT - 12" W.Oak S.9°W., 58.7 ft. mkd: ¼ S16 CS BT.  
Rescribed-16" W.Oak N.15°W., 23.1 ft. mkd: ¼ S9 CS BT.

---

Found OK Dec. 1993 by M.Heimburger - M119-13  
Found Ok Jan. 1994 by B.Shaner - RM 3-80 & CS 63/154-1  
Found Ok Nov. 1998 by G.Lang - 1999-0017  
Found ok July 2009 by N. Hibbs - 2009-0047