

PRIMARY CORNER DESCRIPTION M.C. on N-S center line Sec. 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO subdivision of Sec. 9 by Fred Mensch Under Special Instructions dated July 14, 1924 (DCSO records Volume 11 Page 4413)

Set an Iron post, 3 ft. long, 1" dia., 27" in the ground for special meander cor. of sec. 9, with brass cap mkd.

S M C
C/
/S | 9
1924

from which

An Ash 11" dia., bears South 24 lks. dist., mkd.
S 9 S M C BT.

A Dogwood 7" dia., bears S.48½°W., 33 lks. dist.
mkd. S 9 S M C BT.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jerry Layne - Jan. 1966 - C.S. File 54/7-3

Found - 1924 GLO Brass cap, firmly set & mkd: S MC S9.
11" now 13" Ash, South 15.8 ft., shows scribe on partially healed scar.
No trace of other BT.

New BT - 11" W.Oak S.65°E., 22.2 ft. mkd: S MC S9 CS BT.
This cor. lies approx. 50 ft. North of road, course NE & SW

Found OK, BLM resurvey by Berry, 1972 (DCSO records, Vol. 39 Page 15920)

Doug. County Surveyors Office - Larry Monrean, Deputy; T.R. Plouff - April 1, 1981 - C.S. File 61/19-22

Found - 1924 GLO brass cap monument out of ground near BT described below. Cap is stamped SMC S9| & is attached to a 1" x 36" Iron pipe.
No original BTs found.
A W.Oak 11" now 14" with well healed double blaze bears S.65°E., 22.2 ft. (This is the only BT found.)

We set a temporary marker at corner position (in log extending out over the water) and find:

(Cont. Next Page)

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 340512

PRIMARY CORNER DESCRIPTION M.C. left bank, N-S C/L Sec. 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A 16" Ash bearing South 18.8 ft. (Rec. South 15.8 ft.) with BLM boundary tag attached. We are not able to locate any evidence of blaze, scribing or axe work. Along with noted difference of record dist., we determine that this is not a BT.

As the True Corner position is in the water, WE SET A Witness Corner S.0°56'W., 40.0 ft. from Special Meander Corner on N-S Center sec. line, by survey, using true M S M C corner position and AP #7 (found brass cap) for references. (See 1924 survey and 1972 BLM resurvey.)

Set a 1" x 36" Iron pipe with attached brass cap stamped "Douglas County Surveyor" W.C.
S.M.C.
C
| 40 ft.
/ N
S9 | to cor.
C
T26S R3W 1981

New BTs - 21" DbH D.Fir mkd. X CS BT bears N.76°E., 21.4 ft.
8" DBH I.Cedar mkd. X CS BT bears S.24°W., 44.1 ft.
20" DBH D.Fir mkd. X CS BT bears S.75°W., 28.5 ft.
22" DBH D.Fir mkd. X CS BT bears N.27°W., 9.3 ft.

(A Sketch is attached to field notes in CS File)

Douglas Co. Surveyors Office - John Pike - Stephen J. Flauser -
3/3/2008 - C.S. File 67/25-29

Fd. Ok, 3 live BTs, 1 snag.