

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 340540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey subdivision of sec. 9 by Fred Mensch
Under Special Instructions dated July 14, 1924 (DCSO
records, Volume 11 Page 4412)

Set an Iron post, 3 ft. long, 1" dia., 28" in the ground, for
center 1/4 cor. of sec. 9, with brass cap marked:

C ¼ S 9
1924

from which

A W.Oak 7" dia., bears S.16°E., 7 lks. dist. mkd.
C ¼ S 9 B T.

A B.Oak 8" dia., bears N.47°W., 8 lks. dist., mkd.
C ¼ S 9 B T.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone;
Jerry Layne - Jan. 1966 - C.S. File 54/7-7

Found - 1024 GLO Brass cap.
7" now 11" W.Oak S.16°E., 4.6 ft., shows faint scar,
dying. We do not open.
8" now 16" B.Oak N.47°W., 5.3 ft. shows scar, alive
& in good condition. We do not open.

New BTs - 11" D.Fir N.70°E., 26.4 ft. mkd. "C ¼ S9 CS BT".
Rescribe 16" B.Oak N.47°W., 5.3 ft. mkd. "C¼ S9 CSBT"
Corner lies in N-S fence line.