

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Addison R. Flint, Under Contract #55, dated March 1855 (DCSO records Volume 10 Page 4364)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Laurel 7" dia., bears S.27°E., 18 lks. dist. A B.Oak 4" dia., bears N.88°W., 19 lks. dist.</p>
<p>GLO resurvey by Fred Mensch, Under Special Instructions dated July 14, 1924 (DCSO records, Vol. 11 Page 4407)</p> <p>-----</p> <p>Proportional measurement, Set an Iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor., with brass cap mkd: ¼ $\frac{S\ 4}{S\ 9}$ 1924 from which A Fir 14" dia., bears N.47°E., 6 lks dist. mkd. ¼ S4 BT. A Fir 14" dia., bears S.69°W., 29 lks., mkd. ¼ S9 BT.</p>
<p>Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jerry Layne - Jan. 1966 - C.S. File 54/7-9</p> <p>-----</p> <p>Found - 1924 GLO brass cap pushed out of place & buried. 14" now 24" Fir stump N.47°E., 4.0 ft., shows good scar. 14" now 24" Fir S.69°W., 19.1 ft. Alive, previously opened & shows good "S" & parts of other scribe Reset GLO brass cap at corner point. New BTs - 10" D.Fir S.58½°W., 40.2 ft. mkd. ¼ S9 CS BT. 7" D.Fir N.38°E., 66.0 ft. mkd. ¼ S4 CS BT. Fence corner bears N.47°E., 5.0 ft., fences E-W and S.</p>
<p>Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 11/6/2007 - C.S. File 67/24-44</p> <p>-----</p> <p>Found ok, both new BTs from 1966 DCSO renewal live & healthy</p>
<p>Adam DeGroot - For: Dollens & Strader - Dec. 2020 - M178-27</p> <p>-----</p> <p>Found - A 1" iron post by Mensch in 1924 per USGLO survey of sec. 9, firmly set & projecting 12" above the ground in a 12" stone collar with a 2½" brass cap properly mkd per the record 25" D.Fir bears N.38°15'E., 65.5 ft w/charred healed dbl blaze (N.38°E., 66.0') 1966 A 31" D.Fir bears S.57°45'W., 39.9 ft w/charred healed dbl blaze (S.58°30'W., 40.2')1966 continued next page</p>

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- A 15" maple bears S.71°15'E., 15.3 ft bark scribed
"¼ S9 BT"

A 14" D.Fir bears N.65°30'W., 22.1 ft scribed "¼ S4
BT" on dbl blaze

Note - Corner falls 5 feet south of dilapidated E-W fence
line, in low intensity burn area - BTs are alive
and trunks charred 15-20 feet high.