TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias Description
Alias Description
Alias Description
Alias Description

Original - Addison R. Flint, Under Contract #55, dated March 1855 (DCSO records Volume 10 Page 4356)

Set ¼ sec. post, from which
A B.Oak 7" dia., bears S.62°W., 240 lks. dist.
A B.Oak 6" dia., bears S.40°E., 150 lks. dist.

Bureau of Land Management Resurvey by Berry; Popken and Carlson, Group #768 - Survey, June 1972-April 1975 (DCSO records, Volume 37 Page 15403)

Point for the ¼ sec. cor. at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia., 20" in the ground, with brass cap mkd. T 26 S R 3 W
1/4
S 28|S 27
1975
from which
A Fir 28" dia., bears S.84°E., 11 lks., mkd. ¼ S27 BT.
A Fir 9" dia., bears S.47°W., 30 lks., mkd. ¼ S28 BT.

Cor. Fd. & Used in BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group #1608, surveyed July 1991/April 1995 (DCSO records Vol. 51 page 19304)

Ronald Quimby - For: Neil Talcott - May 2007 - M 153-2

Found - BC
37" Fir bears S.84°E., 7.3'
18" Fir bears S.47°W., 19.9'
New - 13" Fir bears S.71°W., 11.8', scribed "¼ S28 BT"
5" cedar bears S.27°E., 16.8', scribed "¼ S28 BT"