

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #55 dated March, 1855  
(DCSO Records, Volume 10 Pages 4355)  
-----  
Set ¼ sec. post, from which  
    A Cedar 8" dia., bears S.83°E., 19 lks. dist.  
    A Red Fir 36" dia., bears S.58°W., 52 lks. dist

Bureau of Land Management resurvey by Beck, White and Reynolds  
Group #'s 242, 491, 527. Survey dated June 1962-Aug. 1963  
(DCSO records, Vol. 32 Page 13383)  
-----  
Point for the ¼ sec. cor., at proportionate distance; there  
is no remaining evidence of the original corner.  
Set an iron post, 28" long 2½" dia., 26" in the ground, with  
brass cap marked:      T 26 S R 3 W  
                                    ¼  
                                    S 21 | S 22  
                                    1962  
  
from which  
    A Fir 20" dia., bears S.72½°E., 32 lks., mkd. ¼ S22 BT.  
    A Fir 16" dia., bears S.25°W., 159 lks., mkd. ¼ S21 BT.

Ken Hoffine - For: Lone Rock Timber Co. - Gary Angiolet &  
Iginaco Roman - 9/2/2009 - C.S. File 65/66-39  
-----  
Found -    BLM BC 0.3 ft. above ground.  
          20" Tall stump bears S.72½°E., 20.9 ft. (record  
          S.72°E., 21.12 ft.) healed face and tag.  
          24" D.Fir bears S.25°W., 104.94 ft. per record did  
          not measure healed face and tag.  
New -      22" D.Fir bears S.43¾°E., 22.1 ft. we scribe ¼ S22  
          BT and tag.  
          16" D.Fir bears N.41½°E., 37.5 ft. we scribe ¼ S21  
          BT and tag.  
Note -     Corner lies on north slope approx. 150 feet north of  
          BLM rock road. Merchantable timber to east. 30  
          foot tall reprod to west.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff  
Lorsung- 2/2/2023 - C.S. File 67/55-36  
-----  
Found -    3¼" BLM brass cap (properly mkd) up 3"  
          Base singed, 44" D.Fir S.25°W., 104.94 ft., fully  
          healed single blaze.  
          Sawn singed 30"x4' D.Fir stump S.43¾°E., 22.0 ft.  
          (rec. 22.1 ft.) blaze burnt out.  
Continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Burnt-dead, 24" D.Fir N.41½°W., 36.8 ft (rec. N.41½°E., 36.8 ft.) fully healed single blaze.

New - 5/8"x30" iron rod with yellow Douglas Co. Surveyors Office plastic cap, N.50°E., 20.9 ft. Up 7".

Note - Corner on North slope approx. 150' North of road.  
Area burnt 9/2020  
Compass decl. 14½°E.

OCRS Coordinate System Cottage Grove - Canyonville Zone  
N 167851.004 E 239552.428

2