

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - A.R. Flint, Under Contract #55 dated March 1, 1855
(DCSO Records, Vol. 10 Page 4355)

Set Post cor. to secs. 15, 16, 21 and 22, from which
A Cedar 17" dia., bears S.35°W., 45 lks. dist.
A Cedar 7" dia., bears S.49°E., 64 lks. dist.
A Cedar 15" dia., bears N.75°E., 23 lks. dist.
A Maple 2" dia., bears N.72°W., 42 lks dist.

Bureau of Land Management resurvey, by White, Beck & Reynolds
Group #'s 242, 491, 527 - Survey June 1962-Aug. 1963
(DCSO records, Vol. 32 Page 13383)

Point for the cor., at proportionate distance; there is no
remaining evidence of the original corner.
Set an Iron post, 28" long, 2½" dia., 26" in the ground, with
brass cap mkd.

T 26 S R 3 W
S 16|S 15
S 21|S 22
1962

from which
A Cedar 12" dia., bears N. 46° E., 90 lks. dist., mkd.
T26S R3W S15 BT.
A Hemlock 27" dia., bears S.34°E., 97 lks. dist., mkd.
T26S R3W S22 BT.
A Hemlock 6" dia., bears S.32°W., 34 lks. dist., mkd.
T26S R3W S21 BT.
A Cedar 13" dia., bears N.11°W., 62 lks. dist., mkd.
T26S R3W S16 BT.

The corner falls in boulder-filled draw, drains E.

Found OK Dec.1993 by M.Heimbürger - M119-13