

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #55 dated March, 1855
(DCSO Records, Volume 10 Page 4355)

Set $\frac{1}{4}$ sec. post, from which
 An Ash 3" dia., bears N.60°W., 12 lks. dist.
 An Ash 2" dia., bears N.25°E., 30 lks. dist.

Bureau of Land Management resurvey, by White; Beck & Reynolds
Under Group #'s 242, 491, 527 - Survey June 1962-Aug. 1963
(DCSO records, Vol. 32 Page 13385)

Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate
distance; there is no remaining evidence of the original cor.
Set an iron post, 28" long, 2 $\frac{1}{2}$ " dia., 26" in the ground, with
brass cap mkd:

T 26 S R 3 W

$\frac{1}{4}$

S 16 | S 15

1962

from which

 A Cedar 10" dia., bears S.84°E., 69 lks. dist.,
 mkd. $\frac{1}{4}$ S15 BT.

 A Cedar 8" dia., bears N.71°W., 48 lks. dist.,
 mkd. $\frac{1}{4}$ S16 BT.

Fd. & Used in BLM Subdivision of Section 15 by Bishop and
Rogers, Group #1207 - July-Sept. 1984 (DCSO records, Vol. 47
Page 17899)

Found OK Dec.1993 by M.Heimbürger - M119-13