

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #55 dated March, 1855
(DCSO Records, Volume 10 Page 4355)

Set post, cor. to secs. 9, 10, 15 and 16, from which
A Red Fir 22" dia., bears N.15°W., 14 lks. dist.
A B.Oak 4" dia., bears N.38°E., 44 lks. dist.
A Sugar Pine 14" dia., bears S.85°E., 24 lks. dist.
A Red Fir 6" dia., bears S.41°W., 10 lks. dist.

W. H. Byars, Under Contract #269, dated July 24, 1877
(DCSO records, Vol. 10 Page 4378)

Post not standing.
Established cor. as per field notes furnished, viz.
A Red Fir 22" dia., bears N.15°W., 14 lks. dist.
Also found the following additional witness trees.
A Red Fir 8" dia., bears S.42°W., 9 lks. dist.
A Sugar Pine 24" dia., bears S.80°E., 22 lks. dist.
No tree in Sec. 10.

G. G. Stewart, Deputy - for: C.J. Green - March 18, 1922
Volume 3 Page 114 (Max Shellabarger and M.L. Kimmel,
Witnesses)

Find the stump of O.B.T. and one O.B.T., a sugar pine
standing.
I reset the corner, putting in a 6" x 6" x 16" stone with a
cut on top for the corner.
I remark a 42" Fir, South, 61.6 lks. Orig. BT.
30" W.Fir N.47°W., 56.0 ft.
Sugar Pine 24" S.80°E., 22 lks. Original BT.
No other tree suitable.

Bureau of Land Management Resurvey, by Fred Mensch, Under
Special Instructions dated July 14, 1924 (DCSO records,
Volume 11, Page 4404)

The point for the cor. of secs. 9, 10, 15 and 16, now marked
by a gate post, point verified by reference to the original
bearing tree in sec. 15, the only original evidence now found,
the other old bearing trees are not found.
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Alongside the gate post, set an Iron post 3 ft. long, 2" dia., 27" in the ground, with brass cap marked:

T 26 S R 3 W	
S 9	S 10

S 16	S 15
1924	

from which

A Sugar pine, 36" dia., bears S.85°E., 24 lks. dist., mkd. BT (the other marks have grown over and I do not uncover them) Old BT.

A Fir 24" dia., bears N.74½°W., 150 lks. dist. marked T26S R3W S9 BT. New BT.

Trees taken by County Surveyor:

A Fir 32" dia., bears S.8°W., 90 lks. dist. marked CS T26S R3W S16 BT.

A Fir 30" dia., bears N.40°W., 93 lks. dist. marked CS T26S R3W S9 BT.

No tree available in sec. 10.

Bureau of Land Management resurvey, by White; Beck & Reynolds Under Special Instructions dated Aug. 9, 1963; April 5, 1940; October 8, 1962. Group #'s 242, 491, & 527. Survey June, 1962-August, 1963 (DCSO records Vol. 32 Page 13386)

Found corner monumented with an old gate post and perpetuated by Fred Mensch, in 1924, with an iron post, 2" dia., firmly set, protruding 9" above the ground.

from which the remains of one original bearing tree

A Sugar pine stump hole with roots and fragments of bark bears S.85°E., 24 lks. dist.

and one bearing tree marked by Mensch in 1924

A Fir stump shell, bears N.74½°W., 150 lks. dist., with fragment of old blaze bearing scribe marks BT.

and County Surveyor's bearing trees, marked by G.G. Stewart in 1922

A sawed Fir stump 42" dia., bears S.8°W., 90 lks. dist., with no apparent marks.

A Fir 36" dia., bears N.40°W., 93 lks. dist., with scribe marks BT on old twisted blaze.

and new bearing trees

A Fir 9" dia., bears N.21°E., 23 lks. dist., mkd. T26S R3W S10 BT.

A Fir 34" dia., bears S.30°E., 66 lks. dist., mkd. T26S R3W S15 BT/

(Cont. Next Page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Cedar, 16" dia., bears S.51½°E., 66 lks. dist., mkd. T26S R3W S15 BT. A Fir 9" dia., bears N.19½°W., 27 lks. dist., mkd. T26S R3W S9 BT.
Found OK Dec. 1993 by M.Heimbürger - M119-13 FD. Ok by N. Hibbs, 10/2008 - 2009-0011A-C