


TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 400534

PRIMARY CORNER DESCRIPTION AP 19 on E Bdy Sec 9

Alias <u>917290</u>	Description <u>AP #19</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original, BLM survey by Daniel Berry, Under Group #796
(DCSO records, Volume 39 Page 15918)

Point for angle point No. 19, 100 ft. normal dist. from
the mean high water lien on the left bank of the North
Umpqua River.
Set an iron post, 28" long, 2½" dia., 24" in the ground,
and in a mound of stone, 2 ft. base, to top, with brass
cap mkd.



from which

A Fir 10" dia., bears North 47 lks. dist., mkd.
AP 19 S9 BT.

A Fir 8" dia., bears N.29°W., 71 lks. dist., mkd.
AP 19 S9 BT.

Doug. County Surveyors Office - Larry E. Monrean, Deputy
Randy Smith - Jan. 25, 1985 - C.S. File 62/25-6

CORNER REPORT ONLY

Found - 1972 BLM brass cap monument set flush with surface
in road fill.
A Fir 10" now 15" dia., has well healed blaze bears
North 31.0 ft.
An 8" dia. Fir with healed blaze bears N.29°W., 45.5
ft. (Rec. 46.9 ft.)
A 1/2" Iron pipe bears N.20°W., 8.2 ft.
A 5/8" dia. Iron Rod in fence corner bears N.1°E.,
7.7 ft.

Found OK Dec. 1993 by M.Heimbürger - M119-13
FD. Ok by N. Hibbs, 10/2008 - 2009-0011A-C

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 2/7/2023 - C.S. File 67/55-46

Found - ¾" BLM brass cap (properly mkd) up 2"
23" D.Fir north 31.0 ft. well healed blaze, add ¾"
mag nail right side center.
12" D.Fir N.29°W., 45.5 ft. healed single blaze,
add ¾" mag nail right side center.

Continued next page

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 400534

PRIMARY CORNER DESCRIPTION AP 19 on E Bdy Sec 9

Alias 917290 Description AP #19

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

A 1/2" iron pipe N.20°W., 8.1 ft. flush with ground.
A 5/8" iron rod in fence cor. N.1°E., 7.5 ft. top bent
up 8".

Note - Area burnt 9/2020
Compass decl. 14½°E.

Lat: 43°19'18.46"N Long: 123°03'02.02"W.