

PRIMARY CORNER DESCRIPTION Sec. Cor. For 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #55 dated March, 1855 (DCSO Records, Volume 10 Page 4354)

- 
- Set post, cor. to secs. 3, 4, 9 and 10, from which
- A B.Oak 8" dia., bears S.45°W., 5 lks. dist.
  - A B.Oak 14" dia., bears N.30°W., 30 lks. dist.
  - A B.Oak 13" dia., bears N.87°E., 33 lks. dist.
  - A W.Oak 12" dia., bears S.33°E., 75 lks. dist.

W.H. Byars, under Contract #269 dated July 24, 1877 - (DCSO records, Vol. 11 Page 4381)

- 
- The cor. to 3, 4, 9 and 10, was not standing. Established cor. as per field notes furnished excepting the witness tree in sec. 4, viz.
- A B.Oak 14" dia., bears N.30°W., 30 lks. dist., Should read 20 lks. dist. instead. (Aug. 1, 1877)

Bureau of Land Management, by Fred Mensch, U.S. Cadastral Surveyor, under Special Instructions dated July 14, 1924 (DCSO records, Vol. 11 Page 4406)

- 
- The point for the cor. of secs. 3, 4, 9 and 10, determined from distance to the original bearing trees, blazes plain, marks overgrown, not opened:
- A B.Oak 22" dia., bears N.87°E., 33 lks. dist.
  - A W.Oak 18" dia., bears S.34°E., 75 lks. dist.
  - A B.Oak 12" dia., bears S.45°W., 5 lks. dist.
  - A B.Oak 20" dia., bears N.22°W., 20 lks. dist.

At the exact cor. point, set an Iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. with brass cap mkd.

T 26	S R 3	W
S 4	S 3	
S 9	S 10	
1924		

from which

- A Fir 10" dia., bears N.58°E., 71 lks. mkd. T26S R3W S3  
BT. New BT.
- A B.Oak 14" dia., bears S.87°E., 67 lks. mkd. T26S R3W S10  
BT. New BT.
- A B.Oak 10" dia., bears S.13°W., 64 lks. mkd. T26S R3W S9  
BT. New BT.
- A W.Oak 5" dia., bears N.24°W., 2 lks., mkd. T26S R3W S4  
BT. New BT.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jerry Layne - January 1966 - C.S. File 54/7-10

Found - 1924 GLO brass cap mkd. "T26S R3W" 1924.  
Continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. For 3, 4, 9, & 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

5" now 7" W.Oak N.24°W., 1.3 ft., alive, shows good scar.  
20" now 24" B.Oak N.22°W., 13.2 ft., shows good scars, alive.  
12" now 19" B.Oak S.45°W., 3.3 ft. shows faint scar, alive.  
10" now 18" B.Oak S.13°W., 42.2 ft., top broken out, shows scar.  
New BTs- 14" D.Fir N.38°E., 18.4 ft. mkd. S9 T26S R3W CSBT.  
12" D.Fir S.20°E., 6.4 ft. mkd. S10 T26S R3W CS BT.  
Corner lies on top of ridge, course NE and SW.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 8/25/1999 - C.S. File 66/12-34  
-----  
Found - 2½" dia., GLO brass cap on a 2" O.D. iron pipe protrudes 12" above ground. 1924  
14" now 26" dia., 2 ft. high Oak stump with illegible reverse scribing visible, bears N.22°W., 13.2 ft. (Agrees with rec.) OBT  
8" now 20" dia., 1 ft. high rotted Oak stump w/axe marks, bears S.45°W. 3.3 ft. (agrees w/rec) OBT  
5" now 8" dia., W.Oak with a fully healed blaze, bears N.24°W., 1.3 ft. (agrees w/rec.) 1924  
14" now down & rotted D.Fir pushed out of position (rec. N.38°E., 18.4 ft.) 1966  
12" now rotted to ground, D.Fir, scribing "10 T26S R3W" bears S.20°E., 6.4 ft. (agrees w/rec.) 1966  
New BTs- 12" dia., Pine double blazed & scribed "T26S R3W S10 CS BT" bears S.13½°E., 32.6 ft.  
12" dia., D.Fir double blazed & scribed "T26S R3W S9 CS BT" bears S.70°W., 57.8 ft.  
10" dia., Pine double blazed & scribed "T26S R3W S3 CS BT" bears N.74½°E., 44.8 ft.  
Note - Where dirt road crest over ridge corner bears N.70°E., 100 ft. ±

Fd. 4 BTs - DCSO, John Pike & Stephen Flause - 3/3/2008 -  
C.S. File 67/25-29

Adam DeGroot - For: Dollens & Strader - Dec. 2020 - M178-27  
-----  
Found - A 2" iron post by Mensch in 1924 per USGLO survey of sec. 9, firmly set & projecting 12' above the ground with a 2½" brass cap properly mkd per the record (oriented east): from which  
A 8" Oak bears record N.24°W., 1.3 ft w/healed blaze (N.24°W., 2 lks) 1924 Continued next pg

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec Cor For 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 21" P.Pine bears N.74°30'E., 45.2 ft. w/charred  
healed dbl blaze (74°30'E., 44.8') 1999  
A 26" P.Pine bears S.14°E., 32.3 ft. w/charred  
healed dbl blaze (S.13°30'E., 32.6') 1999  
A 20" D.Fir bears S.69°30'W., 57.9 ft. w/charred  
healed dbl blaze (S.70°W., 57.8') 1999  
Note - Corner falls in low intensity burn area - BTs are  
alive and trunks charred 15-20 ft high