

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Original - Addison R. Flint, Contract #55 dated March, 1855 (DCSO Records, Volume 10 Page 4354)</p> <p>-----</p> <p>Set ¼ sec. post, from which A B.Oak 18" dia., bears S.14°W., 471 lks. dist. No trees convenient on E side of line.</p>
<p>Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jerry Layne - Jan. 1966 - C.S. File 54/7-11</p> <p>-----</p> <p>Found - Orig. 18" now 21" B.Oak stump, S.14°W., 310.9 ft. Chop out "BT" scribe &amp; reverse from backside. No BT East of line. Set Brass cap at cor. mkd: County Surveyor's Office, 1966 T26S ¼ S4 S3 R3W New BTs- 27" Red Cedar S.22°W., 38.0 ft. mkd. ¼ S4 CS BT. 20" Red Cedar S.42°E., 21.9 ft. mkd. ¼ S3 CS BT. This corner lies on steep south slope.</p>
<p>Fd. 0k - Herman Pieske - Jan. 21,1994 - M118-33</p>
<p>Fd. &amp; used on BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor &amp; Robert H. Browning, Surveying Technician, under Group #1777, surveyed Aug./Sept. 1995 - (DCSO records Vol. 52 Page(s) 19892-3)</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 8/25/1999 - C.S. File 66/12-39</p> <p>-----</p> <p>Found - 2½" dia., brass cap on a 1½" O.D. iron pipe protrudes 12" above ground. 1966 27" now 41" dia., Cedar with a fully healed blaze, bears S.21¼°W., 37.3 ft. (agrees w/rec.) 1966 20" now 25" dia., Cedar with a fully healed blaze bears S.42°E., 21.9 ft. (agrees w/rec.) 1966 New BTs- 6" dia., double blazed &amp; scribed "¼ S4 CS BT" bears N.30°W., 2.8 ft. 5" dia., double blazed &amp; scribed "X BT" bears S.75°E., 11.3 ft. Note - Fences running North &amp; East from a 48" D.Fir bears N.69°E., 44 ft. Fences on cut lines.</p>
<p>Fd. 4 BTs as per 1999 dcso ren. - DCSO, John Pike &amp; Stephen Flause - 3/3/2008 - C.S. File 67/25-29</p>
<p>continued next page</p>

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Adam DeGroot - For: Dollens & Strader - Dec. 2020 - M178-27

-----  
Found - A 1½" iron post by DCSO in 1966, firmly set & projecting 12" above the ground with a 2½" brass cap properly mkd per the record. From which  
1966 BT: A 26" burned Cedar snag bears S.45°E., 21.6 ft, no mks on burned face (S.42°E., 21.9')

1999 BTs -

A 12" burned D.Fir snag bears S.78°15'E., 11.7 ft w/healed dbl blaze (S.75°E., 11.3')

A 15" burned D.Fir snag bears N.44°21'W., 3.03 ft to MAGHUB & brass washer in top of 4 ft high stump (N.30°W., 2.8')

New - A 5/8"x30" iron rod w/2" BTS aluminum cap mkd "RM1 2020" bears N.61°33'16"E., 40.22 ft

A 5/8"x30" iron rod w/2" BTS aluminum cap mkd "RM2 2020" bears N.24°19'25"W., 22.67 FT

Note - Corner falls ±30 feet south of old cat road - located in high intensity burn area - no living trees