

PRIMARY CORNER DESCRIPTION 1/4 Cor Sec. 34; & 3 of T. 27-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 10 Page 4352)

Set ¼ sec. post, from which
 A Pine 12" dia., bears S.5°W., 52 lks. dist.
 A Pine 8" dia., bears N.27°W., 122 lks. dist.

Bureau of Land Management survey by Harold D. Corbin, Group
No. 350, Survey Aug./Nov. 1958 (DCSO records, Volume 29
Page 12413)

Found corner monumented with a wooden post, 3 x 3 ins. cross
section, firmly set, 2½ ft. above ground, and in a mound of
stone, 2½ ft. base, 6" high, at record bearing and distance
from the only remaining original bearing tree:

 A down and rooted Pine 20" dia., bears S.5°W., 52 lks.
 with scribe marks S BT visible on opened blaze.

 At the corner point, set an iron post, 28" long, 2½ ins.
 dia., 24" in the ground, and in a mound of stone,
 2½ ft. base, to top, with brass cap mkd.

 T 26 S R 3 W

 ¼ S 34
 S 3

 1958 from which

 A Cedar 13" dia., bears N.50¾°W., 70 lks. mkd. ¼ S34 BT.

 A Fir 6" dia., bears S.38½°E., 40 lks., mkd. ¼ S3 BT.

Deposit the wood post alongside the iron post.

Fd. OK by B. Shaner, 2/95. M 121-52 - C.S. File 63/161-2

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral
Surveyor, under Group No. 2258, Surveyed April/June 2009 -
(DCSO records Vol. 57 Page(s) 22670)

The ¼ sec. cor. of secs. 3 and 34 on the N. bdy. of the Tp.,
monumented with an iron post, 2½" dia. firmly set, projecting
6" above an embedded collar of stone, with brass cap properly
mkd.

from which the remains of bearing trees mkd. by Corbin

 A fir, 17" dia., bears S.38½°E., 26.4 ft., with a healed
 blaze.

 A sawed cedar stump, 25" dia., bears N.50¾°W., 46.2 ft.
 with a healed blaze.

and a new bearing tree

 A cedar, 9" dia., bears N.70°W., 37.6 ft., mkd. ¼ S34 BT
Corner is located on a N. slope at the intersection of a
dilapidated barbed wire fence line, bears N. and E. **CONT**

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor Sec. 34; & 3 of T. 27-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The geographic position (NAD 1983 (CORS)) of the 1/4 section corner of sections 3 and 34 on the north boundary of the township, as determined by direct occupation, utilizing dual frequency, carrier phase GPS receivers, relative to the National Spatial Reference System (NSRS) Continuously Operating Reference Stations (CORS) "DODSON BUTTE CORS ARP" and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", is as follows:
Latitude: 43°15'25.254"N. Longitude: 123°02'22.978"W.