

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Under Contract #55, dated March 1855 (DCSO records Volume 10 Page 4358)

-----  
Set  $\frac{1}{4}$  sec. post, from which  
    A B.Oak 12" dia., bears S.39°E., 78 lks. dist.  
    A B.Oak 5" dia., bears N.35°W., 50 lks. dist.  
Observed house, S.7°E.

BLM resurvey by Berry; Popken; Carlson, Group #768 - Survey June 1972-April 1975 (DCSO records, Vol. 37 Page 15402)

-----  
Point for the  $\frac{1}{4}$  sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post 28" long,  $2\frac{1}{2}$ " dia., 22" in the ground, with brass cap mkd:  
                    T 26 S R 3 W  
                     $\frac{1}{4}$      $\frac{S 27}{S 34}$

from which  
    A Madrone 10" dia., bears N.12°W., 60 lks. mkd.  $\frac{1}{4}$  S27 BT.  
    A Fir 9" dia., bears S.37°W., 39 lks. mkd.  $\frac{1}{4}$  S34 BT.

Cor. FD. & Used in BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group #1608, surveyed July 1991/April 1995 (DCSO records Vol. 51 page 19300)

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 1/10/2008 - C.S. File 67/25-6

-----  
FD. Ok, 2 live BTs as per rec.