

TOWNSHIP 26 RANGE 03 POINT IDENTIFIER # 440240

PRIMARY CORNER DESCRIPTION C ¼ Cor. Sec. 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group # 1608 - Surveyed July 1991/April 1995 (DCSO Records, Vol. 51 Page 19301)

Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E. and W. centerline.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T26S R3W
C¼ S27
1994

from which the bearing trees mkd. by Alex Tupy, Roseburg District, Bureau of Land Management, in 1977

- A madrone, 13 ins. diam., bears N. 6° E., 101 lks. dist., with healed blaze.
- A pine, 22 ins. diam., bears N. 78° E., 80 lks. dist., with healed blaze.
- A fir, 18 ins. diam., bears S. 35½° E., 37 lks. dist., with healed blaze.

Deposit a white "DEEP-1" magnetic marker at the base. The corner is 0.01 chs. N. of a barbed wire fence, extending E. and W.

From this point, a point established during the course of an administrative survey by Alex Tupy, Roseburg District, Bureau of Land Management, in 1977, bears N. 58° 23' 30" E., 0.015 chs. dist., monumented with an iron pipe, ¾ in. diam., firmly set, projecting 18 ins. above ground. This point was not utilized during the course of this survey, the iron pipe was removed and buried inside the stainless steel post and new bearings and distances were taken to the bearing trees.